

Outdoor Living

Lighting

Outdoor Kitchens and Grills

Outdoor Fireplaces and Pits

Hardscapes

Permeable Pavers

Synthetic Grass

Waterscaping

Introducing... elements™ series

A new offering from Unique Lighting Systems®



An Authentic Style, A Unique Construction.

Unique Lighting Systems®, the leader in brass and copper landscape lighting fixtures, is proud to introduce the Elements™ Series - a high-quality, outdoor lighting portfolio with an advanced alloy construction. This clean and sleek family of fixtures was designed with durability and ease of installation in mind. A sophisticated E-Shield™ process ensures longevity while the innovative FLEX™ Auxiliary Wire Lead provides unmatched flexibility.

**A360
ALLOY**
Superior Corrosion
Resistance

E-Shield™
Powder Coat
6-Year
Anti-Rust
A360 Alloy

**Brass Threaded
Stake**

**Light Logic™
Ready**

**Multiple Transformer
Options Available**



Welcome to Vista Professional Outdoor Lighting, one of the leading suppliers and innovators in the architectural and landscape lighting industry.

Vista has a well-established reputation among lighting designers, engineers, architects, distributors, contractors, and property owners for high quality products and outstanding customer support. Vista's range of innovative designs and finishes are an ideal compliment to residential, commercial, public area, resort and institutional applications.

The charts below help you determine product specifications for all Vista Professional Outdoor Lighting products within this catalog.

STANDARD VISTA FINISHES:

B	Black	HG	Hunter Green
G	Verde	WB	Weather Bronze
BR	Architectural Brick	WI	Weathered Iron
Z	Architectural Bronze	W	White
GT	Granite	BSN	Natural Brass
P	Pewter	BSO	Olde Brass
TC	Terracotta	CSN	Copper
R	Rust	M	Mocha
LZ	Light Bronze	SS	Stainless Steel
DZ	Dark Bronze		

HOW TO SPECIFY: GR-2219-B-BAB-HL

Mounting:	Part No.:	Finish:	Lamp:	Accessories:
GR - ABS ground stake incl.	2219	B - Black G - Verde BR - Architectural Brick Z - Architectural Bronze GT - Granite P - Pewter TC - Terracotta R - Rust LZ - Light Bronze DZ - Dark Bronze HG - Hunter Green WB - Weathered Bronze WI - Weathered Iron W - White BSN - Natural Brass BSO - Olde Brass CSN - Copper M - Mocha SS - Stainless Steel	(Please see lamp order code column on lamp guide, Vista product catalog.)	BL - Flat Cool Blue lens SL - Flat Spread lens FR - Flat Frosted lens DBL - Flat Dark Blue lens GL - Flat Dark Green lens RL - Flat Red lens YL - Flat Amber lens HL - Honeycomb louver

VISTA - UP AND ACCENT LIGHTS, ALUMINUM SERIES

HOUSING: Die-cast, copper-free aluminum

SHROUD: Die-cast, copper-free aluminum fitted to the housing with a silicone o-ring gasket — providing a superior weather-tight seal

SOCKET/LAMP HOLDER: Top grade ceramic socket with nickel contacts, stainless steel springs, and Teflon-jacketed wire leads

WIRING: Prewired with a three-foot pigtail of 18-2 direct-burial cable and underground connectors for a secure connection to the supply cable

GR2216

LAMP: MR-16 Halogen — 50W maximum. LN-20 BAB (20W) Standard

DIMENSIONS: 2 1/2" X 7 1/8"

FINISH: Polyester powder-coated finish available in Black, Verde, Architectural Brick, Architectural Bronze, Light Bronze, Dark Bronze, Granite, Pewter, Terracotta, Rust, Hunter Green, Mocha, Weathered Bronze, Weathered Iron, and White

LENS: Clear or frosted convex glass lens

MOUNTING: ABS ground stake included



GR2219

LAMP TYPE: MR-16 Halogen — 50W maximum. LN-20 BAB (20W) Standard

DIMENSIONS: 2 1/4" X 7 7/8"

FINISH: Polyester powder-coated finish available in Black, Verde, Architectural Brick, Architectural Bronze, Light Bronze, Dark Bronze, Granite, Pewter, Terracotta, Rust, Hunter Green, Mocha, Weathered Bronze, Weathered Iron, and White

LENS: Clear or frosted convex glass lens

MOUNTING: ABS ground stake included



GR5006

LAMP TYPE: MR-16 LED Lamp Only - 36° Flood, 4.5W Standard

DIMENSIONS: 2 5/8" X 5 7/8"

FINISH: Polyester powder-coated finish available in Black, Verde, Architectural Brick, Architectural Bronze, Light Bronze, Dark Bronze, Granite, Pewter, Terracotta, Rust, Hunter Green, Mocha, Weathered Bronze, Weathered Iron, and White

LENS: Clear, tempered, shock and heat-resistant, soda-lime glass lens

OPTICS: Available in 15° Narrow Spot, 25° Spot, 36° Flood, or 60° Wide Flood distributions

MOUNTING: ABS ground stake included



GR5004

LAMP TYPE: MR-11 LED Lamp Only - 36° Flood, 2.5W Standard

DIMENSIONS: 2 1/8" X 5 3/8"

FINISH: Polyester powder-coat finish available in Black, Verde, Architectural Brick, Architectural Bronze, Light Bronze, Dark Bronze, Granite, Pewter, Terracotta, Rust, Hunter Green, Mocha, Weathered Bronze, Weathered Iron, and White

LENS: Clear, tempered, shock and heat-resistant, soda-lime glass lens

OPTICS: Available in 15° Narrow Spot, 25° Spot, 36° Flood, or 60° Wide Flood distributions

MOUNTING: ABS ground stake included



VISTA - UP AND ACCENT LIGHTS, COPPER SERIES



PROFESSIONAL
OUTDOOR LIGHTING

HOUSING: Heavy-gauge, extruded, solid copper housing fitted to a precision CNC-machined, solid brass base. A solid copper lens-retaining flange and high temperature, color-coordinated silicone seal — provides a superior weather-tight seal

SOCKET/LAMP HOLDER: Top grade ceramic socket with nickel contacts, fixed-position design lamp mechanism with stainless steel lamp retaining clip, and Teflon-jacketed wire leads

WIRING: Prewired with a three-foot pigtail of 18-2 direct-burial cable and underground connectors for a secure connection to the supply cable

GR2116CSN

LAMP TYPE: MR-16 Halogen — 35W maximum. LN-20 BAB (20W) Standard

FINISH: Brushed natural copper and brass (Brushed copper will rapidly age to an elegant rich bronze-like color and may develop areas of patina over time.)

LENS: Clear or frosted convex glass lens

DIMENSIONS: 7" X 2"

MOUNTING: ABS ground stake included



GR2104CSN

LAMP TYPE: T3 — 20W maximum. LN-10 T3 Halogen (10W) Standard

FINISH: Natural Copper, Natural Brass, or Olde Brass finish

LENS: Frosted, high-impact, polycarbonate lens

DIMENSIONS: 2 3/8" X 6 7/8", with lamp 5 1/8"

MOUNTING: ABS ground stake included



VISTA - UP AND ACCENT LIGHTS, BRASS SERIES

HOUSING: Machined solid brass

SOCKET/LAMP HOLDER: Top grade ceramic socket with nickel contacts, stainless steel springs, and Teflon-jacketed wire lead

LENS: Clear or frosted convex glass lens

WIRING: Prewired with a three-foot pigtail of 18-2 direct-burial cable and underground connectors for a secure connection to the supply cable

GR2350BSO

LAMP TYPE: MR-16 Halogen — 50W maximum. LN-20 BAB (20W) Standard

FINISH: Natural Brass and Olde Brass

LENS: Clear or frosted convex glass lens

DIMENSIONS: 2 1/2" X 6 3/4"

MOUNTING: ABS ground stake included



VISTA - PATH AND SPREAD FIXTURES, ALUMINUM SERIES

HOUSING: Die-cast, copper-free aluminum

SOCKET/LAMP HOLDER: Top grade ceramic socket with nickel contacts, stainless steel springs, and Teflon-jacketed wire leads

WIRING: Prewired with a three-foot pigtail of 18-2 direct-burial cable and underground connectors for a secure connection to the supply cable

MOUNTING: Bottom of stem threaded with 1/2" NPT

PR4704

LAMP TYPE: T3 — 20W maximum. LN-10 T3 Halogen (10W) Standard

LENS: Clear, high-impact, polycarbonate lens

STEM: 1/2" schedule-40 aluminum pipe with 1/2" NPT

FINISH: Polyester powder-coated finish available in Black, Verde, Architectural Brick, Architectural Bronze, Granite, Pewter, Terracotta, Rust, Hunter Green, Mocha, Weathered Bronze, Weathered Iron, and White

DIMENSIONS: 15 3/4" X 7 3/8"



PR9206B

LAMP TYPE: T3 — 20W maximum. LN-10 T3 Halogen (10W) Standard

LENS: Clear, prismatic, high-impact, polycarbonate spread lens

STEM: 1/2" schedule-40 aluminum pipe with 1/2" NPT

FINISH: Polyester powder-coated finish available in Black, Verde, Architectural Brick, Architectural Bronze, Granite, Pewter, Terracotta, Rust, Hunter Green, Mocha, Weathered Bronze, Weathered Iron and White

DIMENSIONS: 15 1/2" X 10 1/4" x 6 1/2"



VISTA - PATH AND SPREAD FIXTURES, ALUMINUM SERIES (CONT.)

PR4211

LAMP TYPE: T3 — 20W maximum. LN-10 T3 Halogen (10W) Standard

LENS: Clear, high-impact, polycarbonate lens

STEM: 1/4" schedule-40 aluminum pipe with 1/2" NPT custom bushing designed with a stress-dispersing collar, to provide strength and stability for mounting

FINISH: Polyester powder-coated finish available in Black, Verde, Architectural Brick, Architectural Bronze, Granite, Pewter, Terracotta, Rust, Hunter Green, Mocha, Weathered Bronze, Weathered Iron, and White

DIMENSIONS: 17 3/4" X 1 5/8" x 4 5/8"



PR6500

LENS: Clear, high-impact, polycarbonate lens

LAMP TYPE: T3 — 20W maximum. LN-10 T3 Halogen (10W) Standard

STEM: 1/4" schedule-40 aluminum pipe with 1/2" NPT custom bushing designed with a stress-dispersing collar, to provide strength and stability for mounting

FINISH: Polyester powder-coated finish available in Black, Verde, Architectural Brick, Architectural Bronze, Granite, Pewter, Terracotta, Rust, Hunter Green, Mocha, Weathered Bronze, Weathered Iron, and White

DIMENSIONS: 2 1/2" X 21", with 6" shade



PR9216

LAMP TYPE: T3 — 20W maximum. LN-10 T3 Halogen (10W) Standard

LENS: Clear, prismatic, high-impact, polycarbonate spread lens

STEM: 1/2" schedule-40 aluminum pipe with 1/2" NPT

FINISH: Polyester powder-coated finish available in Black, Verde, Architectural Brick, Architectural Bronze, Granite, Pewter, Terracotta, Rust, Hunter Green, Mocha, Weathered Bronze, Weathered Iron, and White

DIMENSIONS: 18" X 10" X 6"



PR7218

LENS: Clear, high-impact, molded, polycarbonate lens

LAMP TYPE: T3 — 20W maximum. LN-10 T3 Halogen (10W) Standard

FINISH: Polyester powder-coated finish available in Black, Verde, Architectural Brick, Architectural Bronze, Granite, Pewter, Terracotta, Rust, Hunter Green, Mocha, Weathered Bronze, Weathered Iron, and White

DIMENSIONS: 6 1/4" X 8 1/8"



VISTA - PATH AND SPREAD LIGHTS, COPPER SERIES



**VISTA
PROFESSIONAL
OUTDOOR
LIGHTING**

HOUSING: Spun solid copper shade with a precision CNC-machined, Twist-to-Lock solid brass lamp base for easy tool-free lamp access

FINISH: Brushed natural copper and brass (Brushed copper will rapidly age to an elegant rich bronze-like color and may develop areas of patina over time)

SOCKET/LAMP HOLDER: Top grade American-made ceramic socket with nickel contacts, stainless steel springs, and Teflon-jacketed wire leads

MOUNTING: Bottom of stem threaded with 1/2" NPT. Fixture may be mounted into threaded hubs in junction boxes, ground stakes, tree-mount boxes, or floor mounting canopies

WIRING: Prewired with a three-foot pigtail of 18-2 direct-burial cable and underground connectors for a secure connection to the supply cable

PR2165CSN

LENS: Clear, optical grade, Pyrex lens for superior beam spread

LAMP TYPE: T3 — 20W maximum. LN-10 T3 Halogen (10W) Standard

DIMENSIONS: 3 3/8" X 16 1/2", with 1 3/8" shade

STEM: 1/2" heavy-gauge, extruded, solid copper pipe with 1/2" NPT





PROFESSIONAL
OUTDOOR LIGHTING

GR5240B

LENS: Lens cover ordered separately, but not required

LAMP TYPE: PAR-36 — 50W maximum. LN-7558 (20W) Standard

HOUSING: Black silicone rubber lamp holder suspended inside a 5" black ABS well

FINISH: Black

SOCKET/LAMP HOLDER: Socket not required. Fixture supplied with high-temperature rated screw terminal spade connectors

MOUNTING: In-grade. Mounting accessories not required

OPTICS/AIMING: Adjustable lamp bracket provides up to 25° of tilt as well as 360° rotation of the housing for precise beam control

DIMENSIONS: 7 3/4" X 5 3/4"



GR5270B

HOUSING: Injection-molded, glass-reinforced Ryton™ R4 composite for strength and high UV stability — warranted for ten years against corrosion

LENS COVER: Injection-molded, glass-reinforced Ryton™ R4 composite fitted to the housing with a silicone o-ring gasket — providing a superior weather-tight seal

FINISH: Available in Black, Verde, Architectural Brick, Light Bronze, Dark Bronze, Granite, Terracotta, Rust, Hunter Green, Mocha, Weathered Bronze, Weathered Iron, and White

SOCKET/LAMP HOLDER: Top grade ceramic socket with nickel contacts, stainless steel springs, and Teflon-jacketed wire leads

LENS: Clear, tempered, shock and heat-resistant, soda-lime glass lens-crowned (convex) to promote water runoff

LAMP TYPE: MR-16 Halogen — 50W maximum. LN-20 BAB/FG (20W) Standard

OPTICS/AIMING: Adjustable lamp bracket (not available with LED) provides up to 25° of tilt as well as 360° rotation of the housing for precise beam control

MOUNTING: In-grade. Conduit mount fixtures have two 3/4" NPT inlets on the bottom

DIMENSIONS: 5" X 4 3/4", with 1/4" grate



GR5272B

HOUSING: Injection-molded, glass-reinforced Ryton™ R4 composite for strength and high UV stability — warranted for ten years against corrosion

LENS COVER: Injection-molded, glass-reinforced Ryton™ R4 composite fitted to the housing with a silicone o-ring gasket — providing a superior weather-tight seal

FINISH: Available in Black, Verde, Architectural Brick, Light Bronze, Dark Bronze, Granite, Terracotta, Rust, Hunter Green, Mocha, Weathered Bronze, Weathered Iron, and White

SOCKET/LAMP HOLDER: Top grade ceramic socket with nickel contacts, stainless steel springs, and Teflon-jacketed wire leads

LENS: Clear, tempered, shock and heat-resistant, soda-lime glass lens-crowned (convex) to promote water runoff

LAMP TYPE: MR-16 Halogen — 50W maximum. LN-20 BAB/FG (20W) Standard

OPTICS/AIMING: Adjustable lamp bracket (not available with LED) provides up to 25° of tilt as well as 360° rotation of the housing for precise beam control

DIMENSIONS: 5" X 4 3/4"

MOUNTING: In-grade



VISTA - SPECIALTY LIGHTS

HOUSING: Die-cast, copper-free aluminum

SHROUD: Die-cast, copper-free aluminum fitted to the housing with a silicone o-ring gasket — providing a superior weather-tight seal

SOCKET/LAMP HOLDER: Top grade American-made ceramic socket with nickel contacts, stainless steel springs, and Teflon-jacketed wire leads

WIRING: Prewired with a three-foot pigtail of 18-2 SPT1 UV-resistant cable and weather-resistant connectors for a secure connection to the supply cable

HT2238

FINISH: Polyester powder-coated finish available in Black, Verde, Architectural Brick, Architectural Bronze, Granite, Pewter, Terracotta, Rust, Hunter Green, Mocha, Weathered Bronze, Weathered Iron, and White

LENS: Clear, tempered, shock and heat-resistant, soda-lime glass lens

LAMP TYPE: MR-16 Halogen — 35W maximum. LN-20 BAB (20W) Standard

MOUNTING: Solid brass loop with 6' stainless steel cable-hanger included

DIMENSIONS: 2 1/4" X 4 3/4"



DL2237

FINISH: Polyester powder-coated finish available in Black, Verde, Architectural Brick, Architectural Bronze, Granite, Pewter, Terracotta, Rust, Hunter Green, Mocha, Weathered Bronze, Weathered Iron, and White

LENS: Clear, tempered, shock and heat-resistant, soda-lime glass lens

LAMP TYPE: MR-16 Halogen — 35W maximum. LN-20 BAB (20W) Standard

MOUNTING: Adjustable bracket and J-box included

DIMENSIONS: 6 3/4" X 2 1/4"



UW4217

HOUSING: Injection-molded Noryl polymer

LENS COVER: Injection molded, polycarbonate lens fitted to the housing with a silicone o-ring gasket — providing a superior watertight seal

FINISH: Available in black only

SOCKET/LAMP HOLDER: Top grade ceramic socket with nickel contacts, stainless steel springs, and Teflon-jacketed wire leads

LENS: Clear, prismatic spread lens with removable mirror-finish reflector to block up light and provide wider horizontal spread

LAMP TYPE: T3 — 20W maximum. LN-10 T3 Halogen (10W) Standard, High Output LED with Vista exclusive smart driver, powered to operate for 50,000 hours

MOUNTING: Internally weighted base for stable placement underwater

WIRING: Prewired with a 15-foot pigtail of 18-3 double jacketed, water-resistant cable including a green ground wire

DIMENSIONS: 5 3/4" X 4 3/4"



**PROFESSIONAL
OUTDOOR LIGHTING**

UW5217

HOUSING: Injection-molded, glass-reinforced Ryton™ R-4 composite for strength and high UV stability — warranted for ten years against corrosion

LENS COVER: Injection molded, polycarbonate lens fitted to the housing with a silicone o-ring gasket — providing a superior watertight seal

FINISH: Available in black only

LAMP TYPE: MR-16 Halogen — 50W maximum. LN-20 BAB/FG (20W) Standard

MOUNTING: Fully adjustable mounting bracket, to provide precise light aiming, mounted on a cement counter weight base for stable placement under water

WIRING: Prewired with a fifteen-foot pigtail of 18-3 double jacketed, water resistant cable including a green ground wire



VISTA - STEP AND BRICK LIGHTING

SL4242

HOUSING: Stamped and formed aluminum recessed box

COVER PLATE: Die-cast, copper-free, aluminum fitted to the recessed box with UV-resistant weather stripping— providing a superior weather-tight seal

FINISH: Polyester powder-coated finish available in Black, Verde, Architectural Brick, Architectural Bronze, Granite, Pewter, Terracotta, Rust, Hunter Green, Mocha, Weathered Bronze, Weathered Iron, and White

SOCKET/LAMP HOLDER: Top grade ceramic socket with nickel contacts, stainless steel springs, and Teflon-jacketed wire leads

LENS: Clear, high-impact, polycarbonate lens

LAMP TYPE: T3 — 20W maximum. LN-10 T3 Halogen (10W) Standard

MOUNTING: Recessed mounting box with easy-to-align system included

DIMENSIONS: 4 3/4" X 2 7/8"



SL4246

HOUSING: Copper free, stamped and formed aluminum recessed box with 1/2" knockouts on the back and side

COVER PLATE: Die-cast, copper-free, aluminum fitted to the recessed box with UV-resistant weather stripping— providing a superior weather-tight seal

FINISH: Polyester powder-coated finish available in Black, Verde, Architectural Brick, Architectural Bronze, Granite, Pewter, Terracotta, Rust, Hunter Green, Mocha, Weathered Bronze, Weathered Iron, and White

SOCKET/LAMP HOLDER: Top grade ceramic socket with nickel contacts, stainless steel springs, and Teflon-jacketed wire leads

LENS: Clear, high impact, polycarbonate lens

LAMP TYPE: T3 (x 2) — 20W maximum. LN-10 T3 Halogen (10W) Standard

MOUNTING: Recessed mounting box included

DIMENSIONS: 9 1/8" X 2 7/8"



SL4243

HOUSING: Die-cast, copper-free, aluminum housing

FINISH: Polyester powder-coated finish available in Black, Verde, Architectural Brick, Architectural Bronze, Granite, Pewter, Terracotta, Rust, Hunter Green, Mocha, Weathered Bronze, Weathered Iron, and White

SOCKET/LAMP HOLDER: Top grade ceramic socket with nickel contacts, stainless steel springs, and Teflon-jacketed wire leads

LENS: Frosted, tempered, shock and heat-resistant soda-lime glass lens

LAMP TYPE: T3 — 20W maximum. LN-10 T3 Halogen (10W) Standard

MOUNTING: Surface mounting plate included, no recessed box required

DIMENSIONS: 3 1/4" X 1 7/8"



SL4260

CHASSIS: Stainless Steel

FLANGE PLATE: Stainless Steel

HOUSING: Aluminum, Stainless Steel, Brass, or Copper

FINISH: Polyester powder-coated finish available in Black, Verde, Architectural Brick, Architectural Bronze, Granite, Pewter, Terracotta, Rust, Hunter Green, Mocha, Weathered Bronze, Weathered Iron, and White

SOCKET/LAMP HOLDER: Top grade Noryl polymer socket with phosphor bronze contacts and PVC-jacketed wire leads. Stainless steel lamp holder

LAMP TYPE: LN-10 T3.5 (10W) Standard. 10W Max





PROFESSIONAL
OUTDOOR LIGHTING

ACCESSORIES

(not all accessories available for all fixtures)

GS150 — 9" black ABS in-ground stake with 1/2" NPT hub

TM150 — Tree mount junction box, black or bronze finish

Optical Effects Lenses	
BL — Flat cool blue lens	RL — Flat red lens
SL — Flat spread lens	YL — Flat amber lens
FR — Flat frosted lens	HL — Honeycomb louver
DBL — Flat dark blue lens	CX — Convex clear lens
GL — Flat dark green lens	CFR — Convex frosted lens
	CBL — Convex cool lens

VISTA - TRANSFORMERS

MT STAINLESS STEEL MULTI-TAP SERIES

Stainless steel, custom-designed, weathertight casing seals components from moisture and debris. Vista's Smudge-Free clear powder-coat ensures a like-brand-new look for years to come.

- ◆ Take-apart stainless steel hinges for easy door removal allowing greater access during installation
- ◆ Water-resistant weatherstripping around door seal
- ◆ Easy to read instructions mounted inside door
- ◆ Magnetic overload circuit breakers for reliable automatic circuit protection under all conditions. A rocker switch may also be used for manual on/off switching
- ◆ Over-sized wiring compartment makes cable installation easy
- ◆ Extra-large terminal strip for multiple low voltage cable connections
- ◆ Separate accessory terminal strip for easy installation of optional photo-cell, motion sensor, or other external switching devices
- ◆ 6', heavy-gauge, grounded, water-resistant power cord with integrally molded plug
- ◆ 120-volt Accessory receptacle for use with optional, removable multi-setting mechanical 24-hour timer or electronic/digital 7-day timer (with battery back-up)
- ◆ Secondary voltage: 11, 12, 13, 14 and 15 volts
- ◆ Lockable, stainless steel latch can be secured to prevent tampering
- ◆ Discrete louvered vents in the rear and sides of the cabinet maintain a cool operating temperature
- ◆ 120-volt terminal strip for easy hardwiring
- ◆ UL Listed to U.S. and Canadian safety standards for landscape lighting transformers (UL 1838)
- ◆ Pool and Spa Ready — Suitable for Use with Submersible Luminaires or Submersible Pumps

TRANSFORMER ACCESSORIES

FPC170 — Vista Photo Cell swivel mount

FPC150 — Vista Photo Cell swivel mount with wiring harness





PROFESSIONAL
OUTDOOR LIGHTING

ES-150 LANDSCAPE SERIES

EXTERIOR CONSTRUCTION: 20-gauge polished, top-grade domestic, 304 stainless steel

FINISH: Polyester powder-coated finish available in Black, Verde, Architectural Brick, Architectural Bronze, Granite, Pewter, Terracotta, Rust, Hunter Green, Mocha, Weathered Bronze, Weathered Iron, and White

TRANSFORMER CHARACTERISTICS: Available Power Rating: 150 Watts
Primary Voltage: 120 Volts
Secondary Voltage: 12 and 15 Volts




PRIMARY PROTECTION: Auto thermal shut-off

SECONDARY PROTECTION: Resettable high performance magnetic circuit breaker

TERMINALS: Extra-large terminal strip for multiple low voltage cable connections

CERTIFICATION: UL Listed to U.S. safety standards for general purpose transformers (UL 1838)

DIMENSIONS:



V-PRO

The new vPRO Transformers are low profile, light weight, stainless steel and utilize solid-state technology. A proprietary, downloadable app allows the transformer to be controlled by any Bluetooth® enabled device.

- ◆ Low profile, light weight, stainless-steel enclosure
- ◆ Ease of handling and installation flexibility
- ◆ Solid-state technology
- ◆ Downloadable app allows control by any Bluetooth® enabled device
- ◆ User-friendly interface for fast, easy set up
- ◆ Astronomic programming with multiple on/off and dimming
- ◆ Smooth dimming from full bright to off
- ◆ On-the-fly override for all control aspects
- ◆ Self-adjusting voltage and current reductions to protect against overload; no breakers to reset
- ◆ Available in single or double circuits; double circuit dimming individually addressable
- ◆ Multiple wattage options from 75 to 500
- ◆ Selectable voltage adjustment (12V or 15V)
- ◆ Outdoor/indoor rated
- ◆ Password protected
- ◆ American made

MODEL	DESCRIPTION
VP-75	Solid State Universal Power Supply 75W Single Circuit
VP-150	Solid State Universal Power Supply 150W Single Circuit
VP-250	Solid State Universal Power Supply 250W Single Circuit
VP-75X2	Solid State Universal Power Supply 150W w/ Dual 75W Circuits
VP-150X2	Solid State Universal Power Supply 300W w/ Dual 150W Circuits
VP-250X2	Solid State Universal Power Supply 500W w/ Dual 250W Circuits





GET EDUCATED & GET THE EDGE ON YOUR COMPETITORS

L I T E

Lighting Institute of Technology & Education

- Industries' leading contractor training and education certification program.
- Contractors will receive certification for:
Intelli-System: Save energy & wire with this low-energy-use, "green" low-voltage lighting system
Power Management System: Maximize proper voltage distribution, consolidate and protect wire connections.
Contractor Referral Program: Qualified Certified contractors will be added to a referral directory accessible by SDSP participants, Developers, Builders, Homeowners, etc.
- Certified Contractors will have access to SDSP services.

SDSP

Specification & Design Support Program

- Industries' leading CAD design training, education & support program.
- Lighting Designers will become more "Green" by learning to design with the Intelli-System & Power Management System to create energy efficient, sustainable and cost-effective lighting designs
- Lighting Designers will receive directory of LITE Certified contractors in their area.

Green Light

Energy Conscious Outdoor Lighting Systems

- Incorporates the use of 24V Low Voltage Lighting Systems with low wattage, long lasting lamps; including replaceable LED lamps.
- More efficient wiring techniques designed to save energy, time & materials.
- Incorporates more flexible glare control techniques for Dark Sky Compliance.

Call your local Unique Lighting Systems, Inc. sales representative for more info today!

Unique Lighting Systems, Inc. 1240 Simpson Way Escondido, CA 92029 (800) 955-4831 www.uniquelighting.com

UNIQUE LIGHTING SYSTEMS®

STANDARD UNIQUE FINISHES:

WB	Weather wBrass	WH	White
NB	Natural Brass	BK	Black
TT	Tucson Tan	VG	Verde Green
BZ	Bronze		

PULSAR

Equipped with four designer lenses, 25' of #16/2 low voltage wire and a Lifetime Warranty the Pulsar is perfect no matter how difficult the challenge..

CONSTRUCTION: Cast Brass

KNUCKLE: Cast Brass, Adjustable with Machined Natural Brass Thumb Screw

SOCKET: Beryllium Copper, pre-greased

SHROUD: Lock and Load, 360 Rotation, 8 Settings

FINISH COAT: Poly-Thermal Shield

MOUNTING: Brown Fusion Stake, Orbital Lock Nut

WIRE: 25', 16/2 THW UV Brown

LAMP: MR-16



Product Code	Description
PULS-NL	Pulsar, No Lamp

The Power of the Demo

Unique Lighting Systems has developed the ultimate sales tool for the landscape lighting professional. This round the clock sales tool allows the homeowner the opportunity to enjoy the beautiful effects of their well lit landscaped home before making their final decision. The demo kit sets up in minutes and comes equipped with everything you need for a lighting presentation.

Features and Benefits of the Demo Kit include:

- ◆ Plug and light. Simply plug in transformer and connect the homerun wires to the hubbed fixtures
- ◆ Unique's exclusive system ensures proper voltage to every fixture every time
- ◆ Quick connects make for speedy set-up and take down. No more wire stripping
- ◆ Features Unique's Multi-Matic transformer and Equalizer Hub wiring
- ◆ Allows you to set up 16 lights in under 15 minutes
- ◆ Helps you sell landscape lighting while allowing you to work on all types of lighting techniques
- ◆ Establish VALUE by giving the homeowner a visual of what a professionally installed landscape lighting job looks like, in turn helping you close the sale



Contact your local Horizon store to get your demo kit!

UNIQUE

LIGHTING SYSTEMS®

STARBURST

This fixture features an unprecedented dual socket mount system allowing you to install a vertical MR16 for directional up-lighting or a horizontal T-3 lamp for wall washing if necessary.

CONSTRUCTION: Cast Brass

SOCKET: Beryllium Copper, pre-greased

FINISH COAT: Poly-Thermal Shield

KNUCKLE: Cast Brass Adjustable with Machined Natural Brass Thumb Screw

MOUNTING: Brown PVC Gravity Stake

WIRE: 25', 16/2 THW UV Brown

LAMP: MR-16, T-3

VOLTAGE: 12 volt



Product Code	Description
STAR-NL	Starburst, No Lamp Included

STELLAR

A miniature version of the Starburst, the Stellar mini wall washer is a powerful fixture. Featuring a small die cast brass body, this undersized power house is able to illuminate planter areas, short retaining walls, step landings or any other area needing a soft glow. Advance applications include under eaves or second story level lighting*.



*(Round Mounting Base needed when installing the Stellar on a surface mount application.)

CONSTRUCTION: Cast Brass

SOCKET: Beryllium Copper, pre-greased

FINISH COAT: Poly-Thermal Shield

KNUCKLE: Cast Brass Adjustable with Machined Natural Brass Thumb Screw

MOUNTING: Brown PVC Gravity Stake

WIRE: 25', 18/2 THW UV Brown

LAMP: T-3

VOLTAGE: 12 volt

MAXIMUM WATTAGE: 20 Watts

Product Code	Description
VALC-NL	Valor , No Lamp

VALOR

Stake Mounted Up Light.

CONSTRUCTION: Precision formed from brass

GASKET: High temperature silicone o-ring (2) for water-tight seal

KNUCKLE: Machined brass knuckle with a solid brass adjustable thumb screw

SHROUD: Precision formed and comes with a factory sealed shock resistant tempered glass lens to prevent water intrusion

LAMP: MR-16



Product Code	Description
STEL-NL	Stellar, No Lamp

GUARDIAN

The Guardian offers style and function without compromise. Its sleek straight lines and dual gasket shroud feature make the Guardian an essential fixture when lighting queen palms, trees, columns or any other tall structure. Equipped with a clear convex lens, 25' of #16/2 low voltage wire and a 15 Year Warranty the Guardian is a perfect choice.

CONSTRUCTION: Natural Copper

KNUCKLE: Cast Brass, Adjustable

SOCKET: Beryllium Copper, pre-greased

FINISH COAT: Poly-Thermal Shield

MOUNTING: Brown PVC Gravity Stake

WIRE: 25', 16/2 THW UV Brown

LAMP: MR-16

VOLTAGE: 12 volt



Product Code	Description
GUAR-NL	Guardian, No lamp

Outdoor Living

UNIQUE LIGHTING SYSTEMS®

UNIQUE - UP AND ACCENT LIGHTS (CONT.)

INTREPID

Sleek straight lines, rotatable shroud feature make the Intrepid an essential fixture when lighting palms, trees, columns or other tall structures. The Intrepid can be also utilized for back lighting, graze lighting, shadow lighting or simply as a directional up light.

CONSTRUCTION: Brass

FINISH: Weathered Brass

SHROUD: 360° Rotation, O-Ring

WIRE: 16/2 Thin UV Brown

SOCKET: Beryllium Copper, pre-greased

LAMP: MR16

LENS: Clear Convex Tempered Lens, Designer lens kit

MOUNTING: Gravity Stake with Orbital Lock Nut 1/2-14 NPSM

VOLTAGE: 12 volt



Product Code	Description
INTR-NL	Intrepid, no lamp

UNIQUE - IN GROUND AND WELL LIGHTS

F100/F200

Unique Lighting carries a full line of powerful in-ground well lights ranging from F100 to the F200. The F-200 uses a PAR 36 35W wide flood lamp to cast an ample beam spread against any landscape element. Its dual cut body allows for surface flush or angled installation options. The featured patented stainless steel gimble ring holds the lamp in place while allowing vertical and horizontal adjustments within the ABS body.

ABS COMPOSITE WELL LIGHTS

Product Code	Description
F200-12-35	Well Light, ABS Composite, Stainless Steel Gimble Ring, 25' Wire Lead and 35W PAR 36 Halogen WFL

PVC COMPOSITE WELL LIGHTS

Product Code	Description
F100-12-35	Well Light, PVC Composite, Rubber Gimble Ring, Grate, 25' Wire Lead and 35W PAR 36 Halogen WFL



UNIQUE - PATH AND SPREAD FIXTURES

CENTAURUS4/CENTAURUS6

The Centaurus offers soft level lighting with an elegant look. The frosted cylindrical lens minimizes glare. The Centaurus is ideal for planter areas, walkways etc.



CONSTRUCTION: Cast and Stamped Solid Brass

FINISH: Weathered Brass (optional finishes available)

MAXIMUM WATTAGE: 20 Watts

SHROUD: Reflective Powder Coat Interior

WIRE: 25' Intelli-Flex wire factory connected

SOCKET: Beryllium Copper, pre-greased with silicon

CONNECTIONS: Anti-Moisture Migration connections

LENS: Frosted Lens

MOUNTING: Stabilizer Stake 1/2-14NPSM

VOLTAGE: 12 volt

Product Code	Description
C4-NL	Centaurus4, No lamp
C6-NL	Centaurus6, No lamp

UNIQUE

LIGHTING SYSTEMS®

ILLUMINATOR4/ILLUMINATOR6

The frosted cylindrical lens minimizes glare while the T-3 lamp provides sufficient light to cast soft glows on any path or walking area. Ideal for walkways, the Illuminator is also perfect for small planter areas in need of light.



CONSTRUCTION: Natural Copper Housing with Machined Brass Collar

SHROUD: Rotating Height Adjustment Settings

SOCKET: Beryllium Copper, pre-greased

FINISH: Poly-Thermal Shield

MOUNTING: Brown PVC Stabilizer Stake

WIRE: 25', 18/2 THW UV Brown

VOLTAGE: 12 volt

Product Code	Description
I4-NL	Illuminator4, No lamp
I6-NL	Illuminator6, No lamp

LANCER4 / LANCER6

The Lancer offers soft level lighting with an elegant look. The frosted cylindrical lens minimizes glare while the T-3 lamp provides sufficient light to cast soft glows on any path or walking area. The Lancer is ideal for planter areas, walkways etc. The adjustable collar gives maximum design flexibility by creating multiple levels of light with one fixture.



CONSTRUCTION: Cast and Stamped Solid Brass

FINISH: Weathered Brass (optional finishes available)

MAXIMUM WATTAGE: 20 Watts

SHROUD: Reflective Powder Coat Interior

WIRE: 25' Intelli-Flex wire factory connected

SOCKET: Beryllium Copper, pre-greased with silicon

CONNECTIONS: Anti-Moisture Migration connections

LENS: Frosted Lens

MOUNTING: Stabilizer Stake 1/2-14NPSM

VOLTAGE: 12 volt

Product Code	Description
L4-NL	Lancer4, No lamp
L6-NL	Lancer6, No lamp

SATURN

Saturn offers soft level lighting with an elegant look. Ideal for walkways, the Saturn is also perfect for when planter areas need lighting. The adjustable settings give maximum design flexibility by creating numerous beam spreads with one fixture.

CONSTRUCTION: Spun Brass with Machined Brass Collar

SHROUD: Adjustable Height Settings

SOCKET: Beryllium Copper, pre-greased

FINISH COAT: Poly-Thermal Shield

MOUNTING: Brown PVC Stabilizer Stake

WIRE: 25', 18/2 THW UV Brown

VOLTAGE: 12 and 24-volt



Product Code	Description
SA-NL	Saturn, No Lamp

CAMBRIDGE

The Cambridge offers soft level lighting with an elegant look. Provides sufficient light to cast soft glows on any path or walking area. Ideal for walkways, the Cambridge is also perfect for when planter areas need lighting. The adjustable settings give maximum design flexibility by creating numerous beam spreads with one fixture.

CONSTRUCTION: Natural Copper with Machined Brass Collar

SHROUD: Adjustable Height Settings

SOCKET: Beryllium Copper, pre-greased

FINISH COAT: Poly-Thermal Shield

MOUNTING: Brown PVC Stabilizer Stake

WIRE: 25', 18/2 THW UV Brown

VOLTAGE: 12 volt



Product Code	Description
CM-NL	Cambridge, No Lamp

UNIQUE LIGHTING SYSTEMS®

CONQUEST

The Conquest is perfect for downlighting with a 360° rotational shroud for glare control. The adjustable brass knuckle allows for perfect directional control.

CONSTRUCTION: Brass

FINISH: Weathered Brass (optional finishes available)

SHROUD: 360° Rotation, O-Ring

KNUCKLE: Adjustable With Thumbnut

WIRE: 25' Intelli-Flex wire factory connected

SOCKET: Beryllium Copper, pre-greased

CONNECTIONS: Anti-Moisture Migration connections

MOUNTING: Brass Mounting Bracket

VOLTAGE: 12 volt

15 Year Warranty



Product Code	Description
CONQ-NL	Conquest, No Lamp

UNIQUE - STEP/BRICK

GEMINI

Perfect for gracing niche surface areas, the Gemini offers a half dome lock and load cover directing parallel light output while concealing all mounting hardware. It's frosted designer lens softens the beam spread to create a warm glow while still powerful enough to provide safety and security.



CONSTRUCTION: Cast Brass

SOCKET: Beryllium Copper, pre-greased

SHROUD: Lock and Load, Fully Rotatable

FINISH COAT: Poly-Thermal Shield

MOUNTING: Screws and Anchors/Surface Mount

WIRE: 25', 18/2 THW UV Brown

VOLTAGE: 12 volt

Product Code	Description
GEMI-NL	Gemini, No Lamp

VOYAGER8

The Voyager 8 is a classic recessed step light. Perfect to illuminate stairs, benches, short retaining walls and other niche locations. The Voyager 8 can be ordered with a louvered, open or hooded faceplate to direct and spread light to the intended area.

CONSTRUCTION: Cast Brass Faceplate and Injection Molded, Fully Potted Mount Box

SOCKET: Beryllium Copper, pre-greased

SHROUD: Louver, Open or Hooded (please specify)

FINISH COAT: Poly-Thermal Shield

MOUNTING: Screws and Anchors

WIRE: 25', 18/2 THW UV Brown

VOLTAGE: 12 volt



Product Code	Description
VO8L- NL	Voyager8, No Lamp

VOYAGER5

A smaller version of the Voyager 8, the Voyager 5 is perfect to illuminate stairs, benches, short retaining walls and other niche locations. The Voyager 5 can be ordered with a louvered, open or hooded faceplate to direct and spread light to the intended area.

CONSTRUCTION: Cast Brass Faceplate and Injection Molded, Fully Potted Mount Box

SOCKET: Beryllium Copper, pre-greased

SHROUD: Louver, Open or Hooded (please specify)

FINISH COAT: Poly-Thermal Shield

MOUNTING: Screws and Anchors

WIRE: 25', 18/2 THW UV Brown

MAXIMUM WATTAGE: 20 Watts

VOLTAGE: 12 volt

Lifetime Warranty



Product Code	Description
VO5L	Voyager5, No Lamp

SOVEREIGN

The Sovereign is a step beyond the normal recessed step light. Perfect to illuminate stairs, benches, short retaining walls and other niche locations. The Sovereign pane and louvered cover direct and spread light to the intended area. The mounting box secures the fixture while still allowing face plate adjustments.

CONSTRUCTION: Brass Faceplate/Composite Box

FINISH: Weathered Brass

FACE PLATE: Louver with Level Adjustment Plate

WIRE: 25' Intelli-Flex wire factory connected and potted

CONNECTIONS: Fully potted

MOUNTING: Recessed

VOLTAGE: 12 volt

15 Year Warranty

Product Code	Description
S5FL-NL	Sovereign 5 — 6"
S8FL-NL	Sovereign 8 — 9.5"



WHAT SETS US APART

The Hub System



For over 20 years Unique Lighting Systems® has provided leadership and distinguished itself as innovators in the low voltage lighting industry. Our patented HUB system sets the benchmark within the industry and continues to be the best solution for saving time and money.

Wire connections are the weakest point of any low voltage installation and are susceptible to wicking and water infiltration. Utilizing the HUB installation method will reduce the number of connections by up to 80% versus standard wiring methods. This means less maintenance, less lamp outages and easier troubleshooting. In addition the HUB method utilizes less wire and saves money.

Flexibility is essential as landscape continues to grow and change over time. The Elements™ Series features an auxiliary 12" wire lead, in addition to the 15' wire lead, on most fixtures. The new 12" *FLEX™* Auxiliary Lead enables unmatched flexibility and makes expansion easy as trees grow and landscape develops.



Expansion is easy as your landscape grows and changes. The ability to move and add fixtures is easier and faster with the standard 15' wire lead and 12" *FLEX™* Auxiliary Lead.



New landscape:
10' diameter canopy
10' tall tree

Lights placed 18" away from the base of the trunk. Illumination grazes the trunk and fills the canopy.



3 year old landscape:
17' diameter canopy
14' tall tree

Lights moved to 30" away from the base of the trunk. The flexibility provided by the 15' wire lead adapts your lighting to the growing landscape.



7 year old landscape:
20' diameter canopy
17' tall tree

Lights placed 48" away from the base of the trunk. An additional fixture is added using the *FLEX™* Auxiliary Lead without having to run new wires.

UNIQUE LIGHTING SYSTEMS®

PHOTON

The Photon® fixture is designed primarily as an uplight. Due to its smaller size, this fixture is ideal for achieving an elegant lighting effect in small, tight spaces.

- ◆ Marine grade A360 alloy construction
- ◆ 15' hub-ready wire lead
- ◆ 12" *FLEX*™ Auxiliary Lead
- ◆ Composite stake with molded brass threaded insert
- ◆ Available in shrouded and non-shrouded version
- ◆ Dual silicone o-ring seal
- ◆ Accepts Unique's *FLEX*™ Series LED MR11 lamps or halogen lamps

DIMENSION: • 2.25" diameter x 6.25" length
• 2" diameter x 4.75" length

FIXTURE ORDERING INFORMATION

Example: PHOS-NL-BK (Photon Shrouded, No Lamp, Black)

Model Name	Wattage	Finish
PHOS = Shrouded	NL = No Lamp	BK = Black
PHOT = No Shroud		BZ = Bronze
		TT = Tuscan Tan

NUCLEUS

The Nucleus® fixture is designed to illuminate shrubs, trees, signage, architectural facades and more.

- ◆ Marine grade A360 alloy construction
- ◆ 15' hub-ready wire lead
- ◆ 12" *FLEX*™ Auxiliary Lead
- ◆ Composite stake with molded brass threaded insert
- ◆ Available in shrouded and non-shrouded version
- ◆ Dual silicone o-ring seal
- ◆ Accepts Unique's *FLEX*™ Series LED MR16 lamps or halogen lamps

DIMENSION: • 3.3" diameter x 6.8" length
• 2.75" diameter x 4.72" length

FIXTURE ORDERING INFORMATION

Example: NUCL-NL-BK (Nucleus Shrouded, No Lamp, Black)

Model Name	Wattage	Finish
NUCS = Shrouded	NL = No Lamp	BK = Black
NUCL = No Shroud		BZ = Bronze
		TT = Tuscan Tan



GAMMA RAY

The Gamma Ray® fixture is economically priced yet maintains Unique's high standards of quality components, superior finishes, and lasting performance - making it the perfect selection for any value engineered project.

- ◆ Marine grade A360 alloy construction
- ◆ 3' wire lead
- ◆ Composite stake with molded brass threaded insert
- ◆ Available in shrouded version
- ◆ Silicone o-ring seal
- ◆ Accepts Unique's *FLEX*™ Series LED MR16 lamps or halogen lamps

DIMENSION: 2.5" diameter x 6.7" length

FIXTURE ORDERING INFORMATION

Example: GAMS-NL-BK (Gamma Ray Shrouded, No Lamp, Black)

Model Name	Wattage	Finish
GAMS = Shrouded	NL = No Lamp	BK = Black
		BZ = Bronze
		TT = Tuscan Tan



ORBITAL

The Orbital® fixture is designed to mimic the soft, inviting glow of moonlight. The installation height of these fixtures allows their illumination to expand broadly across outdoor areas and gently sway with the wind, casting subtle shadows just as natural light would.

- ◆ Marine grade A360 alloy construction
- ◆ Hangs from 15' hub-ready wire lead
- ◆ 12" *FLEX*™ Auxiliary Lead
- ◆ Silicone o-ring seal
- ◆ Petite 5" height
- ◆ Accepts Unique's *FLEX*™ Series LED MR11 lamps or halogen lamps

DIMENSION: 3.03" diameter x 4.92" height

FIXTURE ORDERING INFORMATION

Example: ORBI-NL-BK (Orbital Shrouded, No Lamp, Black)

Model Name	Wattage	Finish
ORBI	NL = No Lamp	BK = Black
		BZ = Bronze



UNIQUE

LIGHTING SYSTEMS®

PROTON

The Proton® fixture features a five inch shroud and is the perfect selection for every intimate garden space, planter area or pathway.

- ◆ Marine grade A360 alloy construction
- ◆ 15' hub-ready wire lead
- ◆ 12" FLEX™ Auxiliary Lead
- ◆ Larger composite stake with molded brass threaded insert
- ◆ White reflection panel under shroud for greater luminence
- ◆ Available in 12" and 18" stem lengths
- ◆ Borosilicate glass lense
- ◆ Accepts Unique's FLEX™ Series LED T3 lamps or halogen lamps

DIMENSION: 5" diameter x 15" or 21" height

FIXTURE ORDERING INFORMATION

Example: PR18-NL-BK (Proton 18" Stem, No Lamp, Black)

Model Name	Wattage	Finish
PR18 = 18" Stem	NL = No Lamp	BK = Black
PR12 = 12" Stem		BZ = Bronze
		TT = Tuscan Tan



ISO

The ISO® fixture is designed for hardscaping installations. It will beautifully illuminate a stone wall, an outdoor bar area or deck.



- ◆ 18 guage AL 1060 aluminum sheet
- ◆ 6' wire lead
- ◆ Available with 2700K or 3000K integrated LEDs
- ◆ 40,000 hour LED lifespan
- ◆ Easily retrofit with two bendable tabs to secure in place
- ◆ Slim 1/2" construction will tuck into any ledge or cantilever
- ◆ LED compartment is sealed and water resistant
- ◆ Black or bronze powder coat finish

DIMENSION: 5.875" wide x 2.75" length x .5" height

FIXTURE ORDERING INFORMATION

Models

IS6-LED-27k-BK

IS6-LED-30k-BK

IS6-LED-27k-BZ

IS6-LED-30k-BZ



NEUTRON

The Neutron® features a larger seven inch shroud to further increase spread performance. It is perfect for pathways, area lighting or planters.

- ◆ Marine grade A360 alloy construction
- ◆ 15' hub-ready wire lead
- ◆ 12" FLEX™ Auxiliary Lead
- ◆ Larger composite stake with molded brass threaded insert
- ◆ White reflection panel under shroud for greater luminence
- ◆ Available in 12" and 18" stem lengths
- ◆ Borosilicate glass lense
- ◆ Accepts Unique's FLEX™ Series LED T3 lamps or halogen lamps



DIMENSION: 7" diameter x 15" or 21" height

FIXTURE ORDERING INFORMATION

Example: NU18-NL-BK (Neutron 18" Stem, No Lamp, Black)

Model Name	Wattage	Finish
NU18 = 18" Stem	NL = No Lamp	BK = Black
NU12 = 12" Stem		BZ = Bronze
		TT = Tuscan Tan

UNIQUE LIGHTING SYSTEMS®

INTELLIHUB (INTELLIHUB)

The Intelli-Hub™ is the ultimate In-Line fuse protected wiring system



Includes a replaceable 10, 15 and three 20 Amps fuses allowing you to size the fuse according to load or wire size, thus making troubleshooting accessible, convenient and fast. Includes two Intelli-Connect lugs with greased tubes and five In-Line fuse.

SATELLITE HUB (SHUB)

The Hub System ensures proper voltage distribution and can be used with one or more fixtures.

The Satellite Hub includes three barrel lugs with lithium greased caps and a In-Line 20 amp fuse. The dark brown housing blends discreetly for above or below ground installation.



LUGNUT

Brass Lug Nut

UNIQUE - TRANSFORMERS

UNIQUE LIGHTING SYSTEMS®

MULTI-MATIC TRANSFORMERS

The MULTI-MATIC compensates for voltage drop by allowing the contractor to select from up to eight different voltage taps (12, 13, 14, 15, 16, 17, 18, 20 and 22-volt). This allows the contractor to customize the voltage for each individual run. It's like having eight different transformers in one. With this exclusive feature you may have wire runs up to 800' instead of the traditional short runs of 100' or less, and still get 12-volts to the fixture.



ACCESSORIES

Product Code	Description
SNPC2	Unique Snap-in Photo Cell



Product Code	Description	Finish
360SSSLWB	360 W 12, 13, 14, and 15-volt	Weathered Brass
600SSSLWB	600 W 12, 13, 14, 15, 16, and 17-volt	Weathered Brass
840SSSLWB	840 W 12, 13, 14, 15, 16, 18 and 20-volt	Weathered Brass
1120SSSLWB	1120 W 12, 13, 14, 15, 16, 18, 20 and 22-volt	Weathered Brass
200SSSLLEDWB	200 W 12 and 15-volt	Weathered Brass
300SSSLLSWB	300 W 12 and 15-volt	Weathered Brass

UNIQUE

LIGHTING SYSTEMS®

UNIQUE
LIGHTING SYSTEMS®

Unique Lighting FLEX™ Series LED Lamps

Part Number	Description	Volts	Type	Lumen	CCT	Watts	Lifespan	Beam Spread	Distribution	Volt Amps	List Price
2700K											
LED-2W-M1FL27K-12	MR11, 2W, 2700K, flood, 12V	12	MR11	110	2700K	2	40,000	30	Flood	3.2	\$ 42.00
LED-2W-T327K-12-WR	T3, 2W, 2700K, 12V Water Resistant	12	T3 WR	132	2700K	2.4	40,000	NA	NA	3.0	\$ 40.50
LED2-3W-M6FL27K	MR16, 3W, 2700K, flood, 12V	12	MR16	150	2700K	3	40,000	40	Flood	4.9	\$ 37.25
LED2-3W-M6WF27K	MR16, 3W, 2700K, wide flood, 12V	12	MR16	150	2700K	3	40,000	60	Flood	4.9	\$ 37.25
LED2-4W-M6FL27K	MR16, 4W, 2700K, flood, 12V	12	MR16	220	2700K	4	40,000	40	Flood	5.5	\$ 44.75
LED2-4W-M6SP27K	MR16, 4W, 2700K, spot, 12V	12	MR16	220	2700K	4	40,000	15	Spot	5.5	\$ 44.75
LED2-4W-M6WF27K	MR16, 4W, 2700K, wide flood, 12V	12	MR16	220	2700K	4	40,000	60	Wide Flood	5.5	\$ 44.75
LED-4W-M6FL27K-24	MR16, 4W, 2700K, flood, 24V	24	MR16	190	2700K	4	40,000	34	Flood	5.5	\$ 50.00
LED-4W-M6SP27K-24	MR16, 4W, 2700K, spot, 24V	24	MR16	190	2700K	4	40,000	11	Spot	5.5	\$ 50.00
LED-5W-M6FL27K-12	MR16, 5W, 2700K, flood, 12V	12	MR16	250	2700K	5	40,000	39	Flood	6.6	\$ 60.50
LED-5W-M6FL27K-24	MR16, 5W, 2700K, flood, 24V	24	MR16	250	2700K	5	40,000	39	Flood	6.6	\$ 66.00
LED2-6W-M6FL27K	MR16, 6W, 2700K, flood, 12V	12	MR16	350	2700K	6	40,000	40	Flood	6.9	\$ 87.75
LED2-6W-M6SP27K	MR16, 6W, 2700K, spot, 12V	12	MR16	350	2700K	6	40,000	15	Spot	6.9	\$ 87.75
LED2-6W-M6WF27K	MR16, 6W, 2700K, wide flood, 12V	12	MR16	300	2700K	6	40,000	60	Wide Flood	6.9	\$ 87.75
LED2-8W-M6FL27K	MR16, 8W, 2700K, flood, 12V	12	MR16	500	2700K	8	40,000	40	Flood	9.3	\$ 94.75
LED2-8W-M6SP27K	MR16, 8W, 2700K, spot, 12V	12	MR16	500	2700K	8	40,000	15	Spot	9.3	\$ 94.75
LED2-8W-M6WF27K	MR16, 8W, 2700K, wide flood, 12V	12	MR16	500	2700K	8	40,000	60	Wide Flood	9.3	\$ 94.75
LED-6W-PSP27K-12	PAR36, 6W, 2700K, spot, 12V	12	PAR36	300	2700K	6	40,000	15	Spot	9.7	\$ 94.75
LED-6W-PWF27K-12	PAR36, 6W, 2700K, wide flood, 12V	12	PAR36	300	2700K	6	40,000	32	Wide Flood	9.7	\$ 94.75
LED-10W-PSP27K-12	PAR36, 10W, 2700K, spot, 12V	12	PAR36	400	2700K	9	40,000	15	Spot	14.6	\$ 105.75
LED-10W-PWF27K-12	PAR36, 10W, 2700K, wide flood, 12V	12	PAR36	420	2700K	9	40,000	32	Wide Flood	14.6	\$ 105.75
LED-10W-PWF27K-24	PAR36, 10W, 3000K, wide flood, 24V	24	PAR36	420	2700K	9	40,000	32	Wide Flood	14.6	\$ 115.25
LED-18W-PSP27K-12	PAR36, 18W, 2700K, spot, 12V	12	PAR36	660	2700K	18	40,000	18	spot	26.3	\$ 164.00
LED-18W-PWF27K-12	PAR36, 18W, 2700K, wide flood, 12V	12	PAR36	720	2700K	18	40,000	32	Wide Flood	26.3	\$ 164.00
3000K											
LED-1W-T330K-12	T3, 1W, 3000K, 12V	12	T3	100	3000K	1.5	20,000	NA	NA	2.7	\$ 36.50
LED-2W-T330K-12	T3, 2W, 3000K, 12V	12	T3	200	3000K	2.4	20,000	NA	NA	3.0	\$ 39.25
LED-2W-T330K-24	T3, 2W, 3000K, 24V	24	T3	200	3000K	2.4	20,000	NA	NA	3.0	\$ 44.75
LED-2W-T330K-12-WR	T3, 2W, 3000K, 12V Water Resistant	12	T3 WR	140	3000K	2.4	40,000	NA	NA	3.0	\$ 40.50
LED2-4W-M6FL30K	MR16, 4W, 3000K, flood, 12V	12	MR16	230	3000K	4	40,000	40	Flood	5.5	\$ 44.75
LED2-4W-M6SP30K	MR16, 4W, 3000K, spot, 12V	12	MR16	230	3000K	4	40,000	15	Spot	5.5	\$ 44.75
LED2-4W-M6WF30K	MR16, 4W, 3000K, wide flood, 12V	12	MR16	230	3000K	4	40,000	60	Wide Flood	5.5	\$ 44.75
LED-5W-M6FL30K-12	MR16, 5W, 3000K, flood, 12V	12	MR16	265	3000K	5	40,000	39	Flood	6.6	\$ 60.50
LED2-6W-M6FL30K	MR16, 6W, 3000K, flood, 12V	12	MR16	330	3000K	6	40,000	40	Flood	6.9	\$ 87.75
LED2-8W-M6FL30K	MR16, 8W, 3000K, flood, 12V	12	MR16	500	3000K	8	40,000	40	Flood	9.3	\$ 94.75
LED-6W-PSP30K-12	PAR36, 6W, 3000K, spot, 12V	12	PAR36	335	3000K	6	40,000	15	spot	9.7	\$ 94.75
LED-6W-PWF30K-12	PAR36, 6W, 3000K, side flood, 12V	12	PAR36	335	3000K	6	40,000	32	Wide Flood	9.7	\$ 94.75
LED-10W-PSP30K-12	PAR36, 10W, 3000K, spot, 12V	12	PAR36	443	3000K	9	40,000	15	spot	14.6	\$ 105.75
LED-10W-PWF30K-12	PAR36, 10W, 3000K, side flood, 12V	12	PAR36	450	3000K	9	40,000	32	Wide Flood	14.6	\$ 105.75
LED-18W-PSP30K-12	PAR36, 18W, 3000K, spot, 12V	12	PAR36	690	3000K	18	40,000	18	spot	26.3	\$ 164.00
LED-18W-PWF30K-12	PAR36, 18W, 3000K, side flood, 12V	12	PAR36	750	3000K	18	40,000	32	Wide Flood	26.3	\$ 164.00
5000K											
LED-2W-T350K-12	T3, 2W, 5000K, 12V	12	T3	220	5000K	2.4	20,000	NA	NA	3.0	\$ 39.00
LED2-4W-M6FL50K	MR16, 4W, 5000K, flood, 12V	12	MR16	235	5000K	4	40,000	40	Flood	5.5	\$ 44.75
LED2-6W-M6FL50K	MR16, 6W, 5000K, flood, 12V	12	MR16	390	5000K	6	40,000	40	Flood	6.9	\$ 87.75
LED2-6W-M6WF50K	MR16, 6W, 5000K, wide flood, 12V	12	MR16	385	5000K	6	40,000	60	Wide Flood	6.9	\$ 87.75
LED2-8W-M6FL50K	MR16, 8W, 5000K, flood, 12V	12	MR16	550	3000K	8	40,000	40	Flood	9.3	\$ 94.75
LED-10W-PWF50K-12	PAR36, 10W, 5000K, wide flood, 12V	12	PAR36	550	5000K	9	40,000	32	Wide Flood	14.6	\$ 105.75
LED-18W-PWF50K-12	PAR36, 18W, 5000K, wide flood, 12V	12	PAR36	1012	5000K	18	40,000	32	Wide Flood	26.3	\$ 164.00

UNIQUE LIGHTING SYSTEMS®

FLEX™ SERIES PAR36 LED LAMP 6W, 10W & 18W

- ◆ 40,000 hour rated life at L70
- ◆ IP67 rated
- ◆ Intended for outdoor use, not intended for prolonged submersion in water
- ◆ Up to 85% energy savings when compared to traditional lamps
- ◆ Input voltage 10V-15V
- ◆ Operating temperature from -4° to 122° F
- ◆ No ultra-violet rays to attract insects
- ◆ Mercury-free
- ◆ Five year warranty
- ◆ 18 watt PAR36 not for use in enclosed fixtures

FLEX™ SERIES MR-16 LED LAMP 3W & 4W

- ◆ 40,000 hour rated life at L70
- ◆ 14 year life for average of 8 hours per day
- ◆ Up to 85% energy savings when compared to traditional lamps
- ◆ Input voltage 10V-18V
- ◆ Operating temperature from -4° to 122° F
- ◆ No ultra-violet rays to attract insects
- ◆ Mercury-free
- ◆ Five year warranty

FLEX™ SERIES MR-16 LED LAMP 5W

- ◆ 40,000 hour rated life at L70
- ◆ 14 year life for average of 8 hours per day
- ◆ Up to 85% energy savings when compared to traditional lamps
- ◆ Input voltage 10V-18V
- ◆ Operating temperature from -4° to 122° F
- ◆ No ultra-violet rays to attract insects
- ◆ Mercury-free
- ◆ Five year warranty

FLEX™ SERIES MR-16 LED LAMP 6W & 8W

- ◆ 40,000 hour rated life at L70
- ◆ 14 year life for average of 8 hours per day
- ◆ Up to 85% energy savings when compared to traditional lamps
- ◆ Input voltage 10V-15V
- ◆ Operating temperature from -4° to 122° F
- ◆ No ultra-violet rays to attract insects
- ◆ Mercury-free
- ◆ Five year warranty



FLEX™ SERIES MR-11 LED LAMP

- ◆ 40,000 hour rated life at L70
- ◆ 14 year life for average of 8 hours per day
- ◆ Up to 85% energy savings when compared to traditional lamps
- ◆ Input voltage 10V-18V
- ◆ Operating temperature from -4° to 122° F
- ◆ No ultra-violet rays to attract insects
- ◆ Mercury-free
- ◆ Five year warranty

FLEX™ SERIES T3 LED LAMP

- ◆ 20,000 hour rated life at L70
- ◆ Seven year life for average of eight hours per day
- ◆ Input voltage 10V-18V
- ◆ Operating temperature from -4° to 122° F
- ◆ No ultra-violet ray to attract bugs
- ◆ Mercury-free
- ◆ Five year warranty

FLEX™ SERIES T3 LED LAMP 2W, WATER RESISTANT

- ◆ 40,000 hour rated life at L70
- ◆ 14 year life for average of 8 hours per day
- ◆ Rated for use in open or enclosed fixtures
- ◆ Up to 85% energy savings when compared to traditional lamps
- ◆ Input voltage 10V-18V
- ◆ Operating temperature from -4° to 113° F
- ◆ IP65 rated for outdoor use, not submersible
- ◆ Five year warranty

DESIGNED TO
create a scene



With FX Luminaire, you'll find everything you need to create a perfectly illuminated landscape. From artfully designed LED fixtures made with premium materials, to digital lighting control with the latest technological innovations like zoning, dimming, and Wi-Fi control, FX Luminaire brings it all together.

LANDSCAPE & ARCHITECTURAL LIGHTING | *The Intersection of Art and Engineering*
Learn more. Visit fxl.com

FXLuminaire.

STANDARD FX FINISHES

FXLuminaire

AB	Antique Bronze	FB	Flat Black
AL	Almond	FW	Flat White
AB	Antique Bronze	M	Paintable Matte Gray
AT	Antique Tumbled	NP	Nickel Plate
BS	Natural Brass	SB	Sedora Brown
BZ	Bronze Metallic	SS	Stainless Steel
CB	Camo Bronze	VF	Verde Speckle
CU	Copper	WG	White Gloss
DG	Desert Granite	WI	Weathered Iron
DT	Desert Tan	SV	Silver

LR

Engineered for the client that wants to make a long-term investment in their garden, the LR is without peer. This rugged micro luminaire provides the power and control of the MR-16 lamp family. Through the innovative use of an O-ring hydraulic compression cap seal, the potentially troublesome threads and screws found in other spotlights are eliminated.



DIMENSION: 2.40" X 6"

FINISH: CU, NP

LAMP: MR-16

Product Code	Description
LR	UP Light without glare shield
LR-GS	UP Light with glare shield

MU

The MU is one of the most versatile spotlights on the market and is the perfect choice for the discriminating landscape designer. The MU can be mounted as an uplight or downlight and is the standard for advanced users. A wide variety of effects can be produced by adding our patented RecessorRing®, HexBaffle™ or one of many filters, spread lens or glare control options.



DIMENSION: 2.40" X 7.50"

FINISH: WG, FW, AL, BZ, DG, WI, VF, SB, FB

LAMP: MR-16

Product Code	Description
MU	UP Light

MP

The MP is constructed without compromise using aerospace grade alloys and silicone seals. This super small luminaire is an excellent choice for illuminating small garden elements such as shrubs, boulders and cacti. The MR-11 lamp provides crisp light and high efficiency.



DIMENSION: 1.625" X 5"

FINISH: WG, FW, AL, BZ, DG, WI, VF, SB, FB

LAMP: MR-11

Product Code	Description
MP	UP Light

RS

The RS is a rugged micro luminaire that provides the power and control of the halogen MR-16 lamp family. This precision lighting instrument is a fine example of engineering for simplicity and reliability. Through the innovative use of a G-ring hydraulic compression cap seal, the potentially troublesome threads and screws found in other spotlights are eliminated.



DIMENSION: 2.40" X 6.50"

FINISH: WG, FW, AL, BZ, DG, WI, VF, SB, RB

LAMP: MR-16

Product Code	Description
RS	UP Light

RL

The RL is specifically designed to gently illuminate small scale plant material, boulders, and short garden walls.



DIMENSION: 4" X 6"

FINISH: CU, NP, WG, FW, AL, BZ, DG, WS, VF, SB, FB

LAMP: T3

Product Code	Description
RL	UP Light

PB

The PB is a compact LED wall wash lighting solution. Available in 1 or 3 LED with full color lens options of frosted, blue, amber, and green included. The wider angle of the PB allows a broader lighting option for larger structures and spaces. Engineered with solid construction, yet petite in size.



DIMENSION: 3.9" X 5.5"

MATERIAL: Brass or Aluminum

FINISH: Brass AB, AT, NP, BS, WG, FW, AL, BZ, DG, WI, VF, SB, FB

LAMP: 1LED, 3LED

Product Code	Description
PB	Fixture

FX - UP AND ACCENT LIGHTS

FXLuminaire

FB

Similar in style to its bigger brother the NP, the FB fits nicely into smaller landscapes and tight spaces. Accommodating up to a 3 LED Board, the FB offers all the same up light benefits of the NP in a more compact package.

DIMENSION: 2" X 7.5"

MATERIAL: Aluminum

FINISH: WG, FW, AL, BZ, DG, WI, VF, SB, FB

LAMP: 1LED, 3LED

Product Code	Description
FB	UP Light



QZ

The QZ is the smallest up light offered in the FX LED line. With only a 1LED option it's capable of all the same features and optics of the larger LED up lights like the NP and FB, but in a smaller package.

DIMENSION: 1.75" x 5.75"

MATERIAL: Aluminum

FINISH: WG, FW, AL, BZ, DG, WI, VF, SB, FB

LAMP: 1LED

Product Code	Description
QZ	UP Light



NP

The NP is our most versatile LED up light, and is engineered to accommodate all aspects of your up lighting needs. By coupling the proper light intensity with one of the provided color filters, your designer can fine-tune the NP to beautifully enhance every landscape feature.

DIMENSION: 2.66" x 8.38"

MATERIAL: Aluminum

FINISH: WG, FW, AL, BZ, DG, WI, VF, SB, FB

LAMP: 1LED, 3LED, 6LED, 9LED

Product Code	Description
NP	UP Light



FX - PATH AND SPREAD FIXTURES

DM

For those who appreciate the best, this pathway light is designed for both high performance and style. The strong, linear lines of the DM will complement any landscape by day and bring it to life at night. This patent pending luminaire is the best choice for the client who wants a flawless design that will make a long-term contribution to their garden.

DIMENSION: 7.1" x 16.2"

RISER TYPE/HEIGHT: Copper 8", 12", 18", 29", 36"

MATERIAL: Copper/Brass

FINISH: AB, AT, NP, WG, FW, AL, BZ, DG, WI, VF, SB, FB

LAMP: T3, 1 LED, 3 LED

Product Code	Description
DM	Path Light



DL

Milled from extra heavy gauge copper and brass, the DL is engineered to survive. This model is perfect for coastal exposures or areas where irrigation water contains high levels of mineral or caustic salts.

DIMENSION: 6.25" X 15.6"

RISER TYPE/HEIGHT: Copper 8", 12", 18", 24", 36"

MATERIAL: Copper/Brass

FINISH: CU, NP, WG, FL, AL, BZ, DG, WI, VF, SB, FB

LAMP: T3

Product Code	Description
DL	Path Light



SP

Designed for today's crowded planters — the top of the FX Luminaire® SP is just 3.65" in diameter. When incorporated with plant material, the SP simply disappears into the garden.

DIMENSION: 3.62" X 15"

RISER TYPE/HEIGHT: Copper 8", 12", 18", 24", 36"

MATERIAL: Copper/Brass

FINISH: CU, NP, WG, FL, AL, BZ, DG, WI, VF, SB, FB

LAMP: Incandescent

Product Code	Description
SP	Path Light



FX - PATH AND SPREAD FIXTURES (CONT.)

FXLuminaire

CB

Its sophisticated styling and first class quality will add new dimension to any fine landscape. It is no secret why our pathlights are easy to distinguish from the rest.

DIMENSION: 7.4" X 16.2"

RISER TYPE/HEIGHT: Copper 8", 12", 18", 24", 36"

MATERIAL: Copper/Brass

FINISH: AB, AT, CU, NP, WG, FW, AL, BZ, DG, WI, VF, SB, FB

LAMP: T3, 1 LED, 3 LED

Product Code	Description
CB	Path Light

**HC**

The HC offers soft, efficient, and safe lighting solutions for pathways of all shapes, sizes, and locations. With a unique and sleek hat design, durability, and outstanding efficiency, it is the ideal choice for a wide array of path lighting scenarios.

DIMENSION: 3.6" X 15"

RISER TYPE/HEIGHT: Copper 8", 12", 18", 24", 36"

MATERIAL: Copper/Brass

FINISH: AB, AT, CU, NP, WG, FW, AL, BZ, DG, WI, VF, SB, FB

LAMP: 1LED

Product Code	Description
HC	Path Light

**JS**

The JS is a solid path light built to last in the harshest environments and provide efficient illumination. Available in both 1 and 3 LED with the ability to emit soft light that's functional and beautiful, the JS is an excellent path light for many applications.

DIMENSION: 6.3" x 16.5"

RISER TYPE/HEIGHT: Copper 8", 12", 18", 24", 36"

MATERIAL: Copper/Brass

FINISH: AB, AT, NP, CU, WG, FW, AL, BZ, DG, WI, VF, SB, FB

LAMP: 1LED, 3LED

Product Code	Description
JS	Path Light

**TM**

Designed for mid-sized landscapes, the TM provides unmatched elegance and function in the aluminum constructed category. Its small cap provides a stylish presentation, but doesn't compromise on shine. Not only does it accomplish the function of path lighting, it does so with grace and style.

DIMENSION: 5" x 15"

RISER TYPE/HEIGHT: A, 15"

MATERIAL: Aluminum 8", 12", 18", 24", 36"

FINISH: WG, FW, AL, BZ, DG, WI, VF, SB, FB

LAMP: 1LED, 3LED

Product Code	Description
TM	Path Light



FX - DOWN LIGHTS

JB

The JB is FX Luminaire's original LED down light. The JB solves the problem of changing lamps in complicated areas by providing long-life LEDs. The pure color of the LED allows you to add the supplied blue lens to create a natural moonlight effect.

DIMENSION: 8.9" x 2.4"

FINISH: WG, FW, AI, BZ, DG, WI, VF, SB, FB

LAMP: 1LED, 3LED

Product Code	Description
JB	Down Light

**LE**

To illuminate a space from above without the need for a large mount a LE can be hung to moonlight areas. Using a hook design, with the included four color filters, illuminate a seating area, under a table umbrella or even from the branch of a tree.

DIMENSION: 1.6" x 3.3"

FINISH: AB, AT, CU, NP, WG, FW, AL, BZ, DG, WI, VF, SB, FB

LAMP: 1LED

Product Code	Description
LE	Down Light



FX - DOWN LIGHTS (CONT.)

FXLuminaire

TC

This fixture is designed to surface mount onto beams or posts. The halogen lamp is adjustable to allow maximum forward projection making this unique model well suited for illuminating steps or color posts from adjacent structures.



DIMENSION: 2.75" X 3.5"

FINISH: CU, NP, WG, FW, AL, BZ, DG, WI, VF, SB, FB

LAMP: Halogen AR-11

Product Code	Description
TC	Down Light

TS

This fixture is an outdoor "track light" giving the exterior lighting designer a full range of previously interior only lighting effects. The mounting base swivels and pivots on nylon bushings allowing for smooth, precise aiming after installation. A 50W TS is available, and is slightly larger than the 20W and 35W fixtures, measuring 6.50" in length.



DIMENSION: 2" x 5" or 2.5" x 6.5"

FINISH: CU, NP, WG, FW, AL, BZ, DG, WI, VF, SB, FB

LAMP: Halogen AR-11 or AR-20

Product Code	Description
TS	Down Light

VL

When a moonlighting effect is desired, but the caliper of a tree is too small to use the TrellisSolare® series specify the FX Luminaire® ViteLume®. The VL uses the same powerful 20W halogen lamp as the TS. This micro downlight hangs from the host tree by a cinch tie requiring no screws or permanent hardware. A small brass hook is also included for beam-mounted applications.



DIMENSION: 2" X 4.50"

FINISH: CU, NP, WG, FW, AL, BZ, DG, WI, VF, SB, FB

LAMP: Halogen AR-11

Product Code	Description
XL	Down Light

FX - WALL LIGHTS

CP

Engineered to bring light to areas such as walkways, stairways and decks as well as to other foot traffic hazards that don't have an adjacent planter area for pathlighting or trees and trellis from which to downlight. Incorporated into the design of the CP is the LevelX feature. The LevelX assures the lighting installer that the faceplates of these permanently mounted fixtures will remain perfectly level upon completion of the installation.



DIMENSION: 5" X 3.50", 3.875" deep

FINISH: AB, AT, CU, NP, WG, FW, AL, BZ, DG, WI, VF, SB, FB

LAMP: T3, 1 LED

Product Code	Description
CP	Wall Light

LM

The patent pending LM is engineered to bring light to areas such as walkways, stairways and decks as well as to other foot traffic hazards that don't have an adjacent planter area for pathlighting or trees and trellis from which to downlight. Some of the features of the LM include a Sleeve that is permanently mounted in concrete or wood wall combined with multiple threaded knockouts and corrosion-free, stainless steel inserts.



DIMENSION: 9.00" X 3.50", 4.00" deep

FINISH: AB, AT, CU, NP, WG, FW, AL, BZ, DG, WI, VF, SB, FB

LAMP: 2XT3, 2 LED

Product Code	Description
LM	Wall Light

MM

To mount, simply drill a 1/4" wireway hole through the post or wall to connect fixture to mainline. Then with the provided screws, attach the MM to the surface. Tempered glass diffuser optics softens the beam spread transition. The MM's narrow profile and wide range of powdercoat options allow it to blend into any surrounding material.



DIMENSION: 3.25" X 1.75"

FINISH: NP, BS, WG, FW, AL, BZ, DG, WI, VF, SB, FB

LAMP: T3

Product Code	Description
MM	Wall Light

FXLuminaire

LF

The LF is our LED under-the-cap hardscape wall light. It can easily be fitted between a block wall and capstone for a neat, clean installation. Due to its modular bracket design, the LF can even be installed under railings and existing construction.

DIMENSION: 6.7" x 3.6" x .9"

FINISH: AB, AT, BS, CU, SS, WG, FW, AL, BZ, DG, WI, VF, SB, FB

LAMP: 1 LED



Product Code	Description
LF	Wall

MS

The MS comes to the FX LED line as an immediate favorite thanks to its close relative the MM. The MS takes all the great features of the MM and adds the energy efficiency and long life of LED. Changeable filters and available in Brass or Powdercoat allow you to add glow at night and during the day.



DIMENSION: 2" x 3.7"

FINISH: AB, AT, NP, BS, WG, FW, AL, BZ, DG, WI, VF, SB, FB

LAMP: 1 LED

Product Code	Description
MS	Wall Light

TRANSFORMERS

PX

Patented PX is available in 300W, 600W and 900W capacities.

- ◆ Heavy gauge stainless steel for long life in corrosive exterior locations
- ◆ Solid power supply for safe, clean power to energy-efficient components
- ◆ Open switching control architecture
- ◆ Multi-tap



Product Code	Description
PX300SS	300W with 3' power cord
PX600SS	600W with 3' power cord
PX900SS	900W with 3' power cord
PXPC	Photocell

LX

The LX Transformer is the industry's first fully digital lighting control transformer. The integrated LCD screen provides current time, photocell, function, and line output readouts. Since its digital display is backlit, adjustments can easily be made 24 hours a day. Including flexible scheduling options and realtime status readouts, the LX provides the ultimate in system reliability and efficiency.



- ◆ Full Digital Control: All functions are controlled by the integrated LCD Screen for a complete real-time output of functions
- ◆ Active Load Draw Bar: Digital Readout of system load usage displayed as a bar in 10% increments
- ◆ Status LEDs: Displays readouts and readiness of the 120V, External Function, Photocell activity, and 12V output
- ◆ 12V Photocell Included and Preinstalled: Smaller size with less wiring

Product Code	Description
LX150M	150W, Digital Control Trans, Matte Gray
LX150SS	150W, Digital Control Trans, Stainless Steel
LX300M	300W, Digital Control Trans, Matte Gray
LX300SS	300W, Digital Control Trans, Stainless Steel

LUXOR

With Luxor controlling an LED landscape lighting system, lights don't simply turn on and off. They come alive. Luxor offers both zoning and dimming capabilities that provide virtually limitless design possibilities..

- ◆ Up to 250 independently adjustable lighting groups can be created
- ◆ Compatible with FX LED ZD lights only
- ◆ All groups can be turned on independently and dimmed from 1-100%
- ◆ No matter where a light is within a system, it can communicate with the transformer to receive its schedule, intensity, and group



Product Code	Description
LZD150M	150W, Dimming Zoning Trans, Matte Gray
LZD150SS	150W, Dimming Zoning Trans, Stainless Steel
LZD300M	300W, Dimming Zoning Trans, Matte Gray
LZD300SS	300W, Dimming Zoning Trans, Stainless Steel

**PRO90 AUTOMATIC CLAMP METER**

- ◆ Fully automatic and hassle free
- ◆ 400A AC, 600V AC/DC, 2000 Ohms measurement
- ◆ Data hold to capture important readings
- ◆ Accessories included: test leads, carrying case



YOUR INVENTORY OF TOOLS FOR LOW-VOLTAGE LIGHTING SHOULD INCLUDE A CLAMP METER AND A DIGITAL MULTIMETER. NOTHING ELSE YOU CAN USE WILL MAKE INSTALLATIONS GO MORE SMOOTHLY AND ENSURE CORRECT VOLTAGES.

PRO30 GENERAL PURPOSE DIGITAL MULTIMETER

Light, compact, easy to use, measures volts, ohms, and current

- ◆ DCV: 0-500V
- ◆ ACV: 0-500V
- ◆ DCA: 0-200mA
- ◆ Resistance: 0-2Mohm
- ◆ Audible continuity: <50ohmDiode test
- ◆ Battery: A23 (included)



VOLTAGE DROP CHARTS ARE AVAILABLE ON OUR WEBSITE AT WWW.HORIZONONLINE.COM

LAMPS**USHIO****MR-11**

Product Code	Description
1000622	FTD MR11 20W 30
1000620	FTC MR11 20W 17
1000628	FTH MR11 35W 30
1000618	USHIO MR-11 HAL
1000615	MR11 FTA Lamp 1
1000626	FTF MR11 35W 20



In addition to the technologically superior MR-16 lamps manufactured by USHIO, smaller halogen mirrored reflectors have also been developed in both MR-11 and MR-8 sizes. These reduced-size, low-voltage MR lamps are ideal for landscape lighting and some of the newer low-profile track lighting systems.

MR-16

Product Code	Description
1000014	BAB MR16 20W 36
1000573	FMW MR16 35W 36
1000370	ESX MR16 20W 12
1000405	EXN MR16 50W 36
1000559	FMV MR16 35W 24
1000592	FNV MR16 50W 60
1000566	FMW MR16 35W 60
1000551	FMT MR16 35W 12
1000430	EXZ MR16 50W 24
1000419	EXT MR16 50W 12
1000004	USHIO MR-16 EUR
1000037	MR16 20W 24D
1000447	EYC MR16 75W 36
1003341	USHIO FMW/FG/WS
1000000	BABJR12V-20W/SL
1000455	EYJ MR16 75W 24



USHIO's halogen 12V PAR 36 lamps are built to withstand the demanding conditions of landscape use while still providing optimum performance in track lighting and retail applications. With a life rating of 4,000 hours and a flame-sealed lens, these lamps are designed to last twice as long as incandescent lamps and are protected against the adverse affects of moisture. Not only do these Halogen lamps provide a longer life than incandescent lamps, they also offer up to 40% more energy savings compared to incandescents, improved lamp to lamp color consistency, and a brighter, whiter light source.

PAR-36

Product Code	Description
1003533	PAR36 35W 30°
1003531	PAR36 20W 30°
1003535	PAR36 35W 8°
1003536	PAR36 50W 30°
1003538	PAR36 50W 8°

**T3 HALOGEN**

Product Code	Description
1000821	T3 20W
1000811	T3 10W
1000833	T3 5W
1000825	USHIO T-3 HALOG
1003085	USHIO T-3 XENON

**T4 HALOGEN**

Product Code	Description
1000823	T4 35W
1000822	USHIO T-4 HALOG
1001430	912 WEDGE 13W
1001433	921 WEDGE 18W



Use the Proper Size Cable

Before you lay any cable, refer to the Cable Size Chart below. This will assist you with matching up the correctly sized cable with the correct minimum gauge of each run.

		CABLE SIZE CHART – 12-VOLT TRANSFORMERS							
		SIZE OF CABLE							
A	25	12	12	12	12	10	10	10	8
B	50	12	12	10	10	8	8	8	0
C	75	12	10	10	8	8	0	0	0
D	100	12	10	8	0	0	0	0	0
E	150	10	8	0	0	0	0	0	0
F	200	10	0	0	0	0	0	0	0
G	250	8	0	0	0	0	0	0	0
H	300	0	0	0	0	0	0	0	0
I	400	0	0	0	0	0	0	0	0

Secrets to Professional Wiring Design

Laying out the Cable


In order to ensure that your installation meets professional standards, we recommend the following:

1. Cluster the fixtures based on the distance from the transformers.
2. Use multiple wire runs to reduce the voltage drop between fixtures.
3. Know your wire capacity. (See Maximum Cable Loads chart)
4. Adhere strictly to the 50' wiring rule. (see wiring diagrams)

MAXIMUM CABLE LOADS			
Wire Size	Rating	Max Usage 80%	Amps
12/2	240 watts	192 watts	16
10/2	360 watts	288 watts	24
8/2	480 watts	384 watts	32

Getting Started

1. Determine the transformer location.
2. Refer to the voltage chart. This will ensure that you don't overload your wire, avoiding excessive voltage drop.
3. Once you have grouped your fixtures into zones, run one cable from the transformer to each zone.



4. It is very important that you observe the 50' wiring rule (see Figs. 1 and 2). The biggest mistake most contractors make is using the Daisy Chain wiring method and allowing too much distance from the first fixture to the last on the wiring run. This causes dim lights at the end of the run due to voltage drop. Instead, use the "T" or "Loop" Wiring Methods. When using the T Method, keep the distance between the middle (home run fixture) and last fixture within 25'. Using the Loop Method, you may extend this distance to 50'. The reason for this is simple: a multi-tap transformer can only control voltage drop to the home run fixture. Voltage drop starts to occur again as the power extends to the remaining fixtures. Observing the 50' wiring rule will prevent the lamps at the end of the run from becoming too dim.

About Voltage Drop

Voltage drop (dim lights) is the biggest problem facing the lighting contractor so it's vitally important that you understand how and why voltage drop occurs.

Where Does Voltage Drop Occur?

1. At the source (where the transformer plugs in) — Most low voltage transformers are designed to operate at a 10:1 ratio. That is, 120V in = 12V out. So if you only have 110V at the outlet you will only have 11V output.
2. At the transformer — Prior to putting a load on the transformer, you will maintain a true 10:1 power ratio. However, as soon as you hook up your wire runs, the transformer will suffer voltage drop and the 12V output may now only be 11V.
3. At the lamps — This is the main reason for voltage drop. The distance of your home run cable, together with the total amount of Ws on the run, will dramatically affect the amount of voltage at the lamps.

None of the lights work.	1.) Is there power at the 120V outlet? 2.) Is the transformer wired directly to a circuit breaker? 3.) Check for secondary voltage at the transformer. 4.) Is the transformer breaker tripped? 5.) Does the unit have a photocell? 6.) Is the timer bad? 7.) Are the bulbs burned out? 8.) Are cable runs connected? 9.) If you have lugs:	Check with voltmeter, or plug in another appliance. Check the plug, check GFI reset button, check circuit breaker. Check and reset the circuit breaker. Using a voltmeter, check for power by connecting to any white and any colored wire. If you have power, skip down to item #7. Turn off power supply and check breaker. If burned out, replace per label instructions. Cover the eye with black electrical tape. Wait a few minutes. If the lights come on, photocell is OK. Remove the timer and plug the white cord into socket. With the unit on, use a voltmeter to check for power at lamps. If power is present, replace the lamp. Check to see that one side of each cable is connected to a white wire, and one connected to a colored wire. Make certain wire is stripped and securely connected.
System comes on for replace photocell. Check with Amp probe.	10. Check photocell. 11.) Check timer. 12.) Check primary breaker.	Cover the eye with black electrical tape. If unit won't come on, or if unit turns off prior to timer off, a short period of time. See timer instructions. If breaker is tripped, check total bulb wattage. If it exceeds 80% of unit capacity, unit may be overloaded.
All lights are dim.	13.) Check voltage at the fixture that wire from the transformer connects to. 14.) Poor connections.	Using the colored wire leads, increase the voltage until you have between 11 and 12 volts. Check for corrosion at all connections and sockets at fixtures.
Lights dim at end of run.	15.) Check distance from first fixture to last.	If more than 50 ft., use the T method of wiring. See wiring instructions for other methods.
Some of the lights work.	16.) Check voltage at each lamp. 17.) Check for interrupted power.	If you have voltage, replace the lamp. Look for bad connections and cut wires somewhere in the loop.
Primary breaker is tripped.	18.) Check total lamp wattage. Total lamp load should not exceed 80% of rated transformer capacity. 19.) Check for shorts in field wiring.	Replace lamps with lamps that have less wattage. Install a higher-wattage transformer. Add another transformer. Disconnect all secondary wiring leads. Now connect one wiring run at a time and check for shorts.


Landscape Low Voltage Lighting

The voltage losses in the chart below were calculated using Ohm's Law, and are theoretical. Safety margin should be built into the design to take into consideration deterioration of wire splices, power brownouts, etc. CONSULT THE MANUFACTURER OF THE LIGHT FIXTURE FOR MORE DETAIL.

- NOTES: 1) Do not use a cable whose ampacity is less than the rating of the transformer circuit breaker.
2) Chart shows voltage drop for maximum flows of 80% of the cables' ampacities.

VOLTAGE DROP PER 10 LINEAR FEET OF CABLE

LAMP POWER FLOWING IN CABLE SECTION (WATTS @ 12V)	FLOW (amps)	WIRE GAUGE (awg), CLASS K COPPER				
		18	16	12	10	8
		WIRE RESISTANCE (Ohms/10' of cable, both conductors) @ 77 °F (25 °C)				
		0.1358	0.0852	0.0336	0.0212	0.0136
20	1.67	0.226	0.142	0.056	0.035	0.023
25	2.08	0.283	0.178	0.070	0.044	0.028
30	2.50	0.340	0.213	0.084	0.053	0.034
35	2.92	0.396	0.249	0.098	0.062	0.040
40	3.33	0.453	0.284	0.112	0.071	0.045
45	3.75	0.509	0.320	0.126	0.080	0.051
50	4.17	0.566	0.355	0.140	0.088	0.057
55	4.58	0.622	0.391	0.154	0.097	0.062
60	5.00	0.679	0.426	0.168	0.106	0.068
65	5.42	0.736	0.462	0.182	0.115	0.074
70	5.83	0.792	0.497	0.196	0.124	0.079
75	6.25	0.849	0.533	0.210	0.133	0.085
80	6.67	0.905	0.568	0.224	0.141	0.091
85	7.08	0.962	0.604	0.238	0.150	0.096
90	7.50	1.019	0.639	0.252	0.159	0.102
95	7.92	1.075	0.675	0.266	0.168	0.108
100	8.33	-	0.710	0.280	0.177	0.113
105	8.75	-	0.746	0.294	0.186	0.119
110	9.17	-	0.781	0.308	0.194	0.124
115	9.58	-	0.817	0.322	0.203	0.130
120	10.00	-	0.852	0.336	0.212	0.136
125	10.42	-	-	0.350	0.221	0.141
130	10.83	-	-	0.364	0.230	0.147
135	11.25	-	-	0.378	0.239	0.153
140	11.67	-	-	0.392	0.247	0.158
145	12.08	-	-	0.406	0.256	0.164
150	12.50	-	-	0.420	0.265	0.170
155	12.92	-	-	0.434	0.274	0.175
160	13.33	-	-	0.448	0.283	0.181
165	13.75	-	-	0.462	0.292	0.187
170	14.17	-	-	0.476	0.300	0.192
175	14.58	-	-	0.490	0.309	0.198
180	15.00	-	-	0.504	0.318	0.204
185	15.42	-	-	0.518	0.327	0.209
190	15.83	-	-	0.532	0.336	0.215
195	16.25	-	-	0.546	0.345	0.221
200	16.67	-	-	0.560	0.353	0.226
205	17.08	-	-	0.574	0.362	0.232
210	17.50	-	-	0.588	0.371	0.238
215	17.92	-	-	0.602	0.380	0.243
220	18.33	-	-	0.616	0.389	0.249
225	18.75	-	-	0.630	0.398	0.255
230	19.17	-	-	0.644	0.406	0.260
235	19.58	-	-	0.658	0.415	0.266
240	20.00	-	-	0.672	0.424	0.272



SUREPRO SKIMMERS AND ACCESSORIES

SurePro skimmers provide an efficient, effective method of maintaining a beautiful water garden. An easy flow-through design combined with simple installation and minimal maintenance offers ideal solution for any existing or new water garden or Koi pond.

- ◆ Makes installing a water garden easier than ever
- ◆ Lockable weir gate restricts water for easier maintenance
- ◆ Bottom siphon port allows for complete water circulation
- ◆ Circular, ridged wall design provides extra strength and in-ground anchoring
- ◆ Molded drill-out ports on both sides provide flexible installation for new or existing ponds
- ◆ Heavy-duty net catches large debris
- ◆ Easy-clean brushes catch smaller debris

2500 GPH SKIMMER

Specification:	SPS2
Width	17.24"
Height	23.25"
Length	21.73"
Gate Width	6.6"
Max GPH	2,500



5000 GPH SKIMMER

Specification:	SPS5
Width	20"
Height	23.0"
Length	26.0"
Gate Width	6.6"
Max GPH	5,000



Standard Pond Calculations:

Liner and Underlayment Sizing

Maximum Depth x 2 + Maximum Length + 3' = Liner Length

Maximum Depth x 2 + Maximum Width + 3' = Liner Width

Calculating Pond Volume

Rectangular Pond Calculation Formula

L = Length of pond in feet, W = Width of pond in feet,
D = Depth of pond in feet

$L \times W \times D \times 7.5 = \text{gals. of pond}$

Example: 10' X 12' X 1.5' depth = 1,350 gals.

Circular Pond Calculation Formula

$(\text{Diameter} \div 2) \times (\text{Diameter} \div 2) \times \text{Depth} \times 23.55$

Example: 15' diameter X 2.5' depth = 3,312 gals.

Recommended Circulation by pond volume:

10,000 GPH SKIMMER

Specifications:	SPS10
Width	24.0"
Height	23.0"
Length	31.5"
Gate Width	9"
Max GPH	10,000



SKIMMER LIDS

Product Code	Description	Used with skimmer
SPS2LG	Lid (granite)	SPS2
SPS2LS	Lid (sandstone)	SPS2
SPS5LG	Lid (granite)	SPS5
SPS5LS	Lid (sandstone)	SPS5
SPS10LG	Lid (granite)	SPS10
SPS10LS	Lid (sandstone)	SPS10

Outdoor Living

SUREPRO - WATERSCAPING EQUIPMENT (CONT.)

ACCESSORIES

Product Code	Description
SPAFV	SurePro Auto Fill Valve Assembly
SPMP2	SurePro Skimmer Matala Pad (2500 GPH)
SPMP5	SurePro Skimmer Matala Pad (5000 GPH)
SPMP10	SurePro Skimmer Matala Pad (10,000 GPH)
SPS2NET	SurePro Skimmer Replacement Net (2500 GPH)
SPS5NET	SurePro Skimmer Replacement Net (5000 GPH)
SPS10NET	SurePro Skimmer Replacement Net (10,000 GPH)

BIOLOGICAL WATERFALL FILTER

SurePro biological waterfall filters are created to mimic a natural waterfall or spring while helping you maintain a balanced ecosystem. Easy to install, our waterfalls are constructed with 14" and 23" waterfall widths and will retrofit into any existing water garden. Utilizing BioVortex™ technology these filters are designed to evenly disperse debris and settle solid bio loads for less maintenance and superior filtration.



- ◆ Corrugated design for extra strength, anchoring and anti-flotation
- ◆ Back flush outlet offers easy maintenance and removal of settling solid bio loads, and helps drain water from the waterfall
- ◆ Molded bottom inlet with 2" bulk head fitting for quick connection
- ◆ Waterfall outlet available in 14" and 23" widths
- ◆ BioVort separator plate creates a cyclone-type up flow to help uniformly separate and evenly disperse debris

Product Code	Description
SPF5	Sur
SPF10	Sur

WATERFALL WEIR

- ◆ Created to mimic a natural waterfall
- ◆ Designed for flows up to 6,000 gals. per hour
- ◆ Constructed with a 7.75" flow opening
- ◆ Built-in drip edge directs water flow and help prevent back flow
- ◆ Circular, ridged wall design provides extra strength and in-ground anchoring



Product Code	Description
SPWF	SurePro Waterfall Weir

LIDS

Product Code	Description	Used with filter
SPF5LG	Lid (Granite)	SurePro BioVortex Filter (5000 GPH)

WEIR

Product Code	Description	Used with filter
SPF5WG	Rock Weir (Granite)	SurePro BioVortex Filter (5000 GPH)
SPF10WG	Rock Weir (Granite)	SurePro BioVortex Filter (10,000 GPH)



ACCESSORIES

Product Code	Description
VSGV150SL	1-1/2" Slide Gate Valve
VSGV200SL	2" Slide Gate Valve
VSGV300SL	3" Slide Gate Valve
VSGV400SL	4" Slide Gate Valve



PONDLESS FOUNTAINS



SIMPLY FALLS™ VAULT

- ◆ For applications when you already have the components to make your water feature, but need something to house your pump
- ◆ 19.25" W X 19.2" L X 24" T vault
- ◆ Vault is rotational molded polyethylene for durability



- ◆ Wall ridges provide added strength
- ◆ Sturdy vault lid allows you to conceal the unit with rocks, gravel, plants, etc
- ◆ Pre-drilled 3" discharge port takes the hassle out of installation
- ◆ Multiple inlet vents allows unit to collect water at a rapid pace

Product Code	Description
SPSF	SurePro Simply Falls Vault

DISAPPEARING BASINS

SUREPRO

- ◆ Heavy duty disappearing water feature basins for in-ground installations
- ◆ Ideal for smaller applications
- ◆ Rugged design holds up in adverse weather conditions
- ◆ Safe for aquatic plants, fish and animals

SPDB36

Specifications:

Width 36"
Height 10.8"
Length 36"
Holding Capacity 35 gals.



Product Code	Description	Maximum Weight Capacity
SPDB36	SurePro Disappearing Basin 36" Round	3,000lbs.

SPDB44

Specifications:

Width 44"
Height 11"
Length 44"
Holding Capacity 60 gals.



Product Code	Description	Maximum Weight Capacity
SPDB44	SurePro Disappearing Basin 44" Square	3,000lbs.

FOUNTAIN PUMPS

SUREPRO

These pumps features an epoxy-encapsulated motor, plastic housing and radial lip seal on the motor shaft. It provides enough power to effectively operate a water garden, statuary, or tabletop fountain. This "potted" pump is usually more compact in size than an oil-filled pump of equal flow capacity.

- ◆ Environmentally safe, oil-less
- ◆ Energy efficient
- ◆ Corrosion resistant body
- ◆ 15' power cord
- ◆ 115V
- ◆ 1/4" MNPT discharge
- ◆ For submersible use only
- ◆ Discharge accepts 1/2" I.D. tubing

SPFP170

- ◆ 170 GPH @ 1' TDH
- ◆ 7' shut-off head
- ◆ 36W

SPFP300

- ◆ 300 GPH @ 1' TDH
- ◆ 12.2' shut-off head
- ◆ 47W

SPFP475

- ◆ 475 GPH @ 1' TDH
- ◆ 13.4' shut-off head
- ◆ 80W



Product Code	Description
SPFP170	SurePro Fountain Pump
SPFP300	SurePro Fountain Pump
SPFP475	SurePro Fountain Pump

DUAL DISCHARGE PUMPS

SUREPRO

This pump utilizes a permanent-split capacitor (PSC) motor sealed in a stainless steel housing, which in turn is surrounded by a plastic case. The PSC motor allows the pump to use less energy than other pumps of similar flow capacity. The motor also develops less heat; therefore, the pump does not require oil internally. This pump is ideal for use in waterfall and stream applications found in water gardens.



SPDDP1250

- ◆ 1250 GPH @ 5' TDH
- ◆ 20' shut-off head
- ◆ 230W
- ◆ 1 1/4" FNPT discharge
- ◆ Handles 1/4" solids
- ◆ 115V
- ◆ 16' power cord

SPDDP4000

- ◆ 4000 GPH @ 5' TDH
- ◆ 30' shut-off head
- ◆ 700W
- ◆ 1 1/4" FNPT discharge
- ◆ Handles 1/4" solids
- ◆ 115V
- ◆ 16' power cord

Product Code	Description	Specification
SPDDP1250	SurePro Dual Discharge Pump	1250 GPH @ 5' TDH
SPDDP4000	SurePro Dual Discharge Pump	4000 GPH @ 5' TDH

Outdoor Living

STAINLESS STEEL PUMPS



SurePro™ water feature pumps are engineered with high quality and structural integrity for optimum efficiency and long life. Constructed with stainless steel, cast iron and durable thermoplastic, each pump meets the rigorous demands of the most impressive water features. The stainless steel cylinder houses a powerful PSC motor and the direct-drive system produces greater starting torque for nearly instantaneous flow. Recommended for Koi and Goldfish ponds as well as features without fish, and for use in conjunction with skimmers and biological waterfall filters for a complete, ecologically balanced system.

SPSSP2300

- ◆ 2300 GPH @ 5' TDH
- ◆ 21' shut-off head
- ◆ 355W
- ◆ 1 1/4" FNPT discharge
- ◆ Handles 3/8" solids
- ◆ 115V
- ◆ 19' power cord



SPSSP4280

- ◆ 4280 GPH @ 5' TDH
- ◆ 30' shut-off head
- ◆ 590W
- ◆ 2" FNPT discharge
- ◆ Handles 1 3/16" solids
- ◆ 115V
- ◆ 19' power cord



SPSSP6400

- ◆ 6400 GPH @ 5' TDH
- ◆ 35' shut-off head
- ◆ 1210W
- ◆ 2" FNPT discharge
- ◆ Handles 1 3/8" solids
- ◆ 115V
- ◆ 19' power cord



Product Code	Description	Specification
SPSSP2300	SurePro Stainless Steel Pump	2300 GPH @ 5' TDH
SPSSP4280	SurePro Stainless Steel Pump	4280 GPH @ 5' TDH
SPSSP6400	SurePro Stainless Steel Pump	6400 GPH @ 5' TDH

LittleGIANT®

This pump has been designed to operate in applications such as waterfalls, streams, and fountainheads. It can also be used to circulate the water in your pond. Unique features of this pump include a non-clogging vortex impeller, auto resetting thermal overload protection, stainless steel motor housing, and the ability to pass solids with diameters up to 1.18"/30mm (WGFP-50) or 1.38"/35mm (WPGF-75, WGFP-100, WGFP-150, and WPGF-200).

CAUTION: To prevent damaging the pump, do not pump abrasives such as sand or mud.



Product Code	Description
566061	WGFP-150 9750GPH @ 5', 1210 WATTS, 19' CORD, 3/4" SOLIDS
566072	WGFP-200 16000GPH @ 5', 2085 WATTS, 19' CORD, 3/4" SOLIDS
566724	1200GPH PUMP 115V 60HZ 20FT

WATER FEATURE PUMPS

LittleGIANT®

The F-Series pumps provide circulating, oxygenated water to features such as ponds fountains, displays, waterfalls and filter systems.



Product Code	Description
566726	WGFP-150 9750GPH @ 5', 1210 WATTS, 19' CORD, 3/4" SOLIDS
566728	WGFP-200 16000GPH @ 5', 2085 WATTS, 19' CORD, 3/4" SOLIDS
566729	1200GPH PUMP 115V 60HZ 20FT



LOW WATER LEVEL CUT-OFF SWITCH

- ◆ Converts any manual pump, up through 1/2 hp (10 max. run Amps), to automatic
- ◆ 115V Pump Cut-off Switch
- ◆ 18' Power Cord

Product Code	Description
SPLWLS	SurePro Low Water Level Cut-Off Switch



HIGH FLOW ENERGY EFFICIENT POND CIRCULATION PUMPS



The SPOPES & SPOESHH Energy Saving pumps are the benchmark for today's pond industry. These pumps have true 3" suction and discharge fittings and are fitted with energy saving motors. With their advanced technology, the SPOPES & SPOESHH have whisper quiet operations with tremendous flow rates. Offered in both high flow as well as high head designs. These pumps are designed for out of pond applications and are not for use as submersible pumps.

SPOPES10500


- ◆ 10,500 GPH @ 5' TDH
- ◆ 35' shut-off head
- ◆ 540W
- ◆ 3" FNPT discharge
- ◆ Handles 1/8" solids
- ◆ 115V
- ◆ 15' power cord

SPOPES12500

- ◆ 12,500 GPH @ 5' TDH
- ◆ 38' shut-off head
- ◆ 814W
- ◆ 3" FNPT discharge
- ◆ Handles 1/8" solids
- ◆ 115V
- ◆ 15' power cord

SPOPES16500

- ◆ 16,500 GPH @ 5' TDH
- ◆ 44' shut-off head
- ◆ 1309W
- ◆ 3" FNPT discharge
- ◆ Handles 1/8" solids
- ◆ 115V
- ◆ 15' power cord



Product Code	Description	Specification
PTES10500	SurePro Energy Saver Out of Pond Pump	10,500 GPH @ 5' TDH
PTES12500	SurePro Energy Saver Out of Pond Pump	12,500 GPH @ 5' TDH
PTES16500	SurePro Energy Saver Out of Pond Pump	16,500 GPH @ 5' TDH

Outdoor Living

ENERGY SAVER PUMP

SUREPRO

The SPOP Series water garden pump is the most energy efficient pump on the market. With its extremely quiet operation and low energy consumption it is the perfect choice for today's discerning pond builder. These pumps are designed for out of pond applications and are not for use as submersible pumps.



SPOP3500

- ◆ 3500 GPH @ 5' TDH
- ◆ 18' shut-off head
- ◆ 143W
- ◆ 2" FNPT discharge
- ◆ Handles 1/8" solids
- ◆ 115V
- ◆ 15' power cord

SPOP5500


- ◆ 5500 GPH @ 5' TDH
- ◆ 20' shut-off head
- ◆ 286W
- ◆ 2" FNPT discharge
- ◆ Handles 1/8" solids
- ◆ 115V
- ◆ 15' power cord

SPOP4500

- ◆ 4500 GPH @ 5' TDH
- ◆ 19' shut-off head
- ◆ 187W
- ◆ 2" FNPT discharge
- ◆ Handles 1/8" solids
- ◆ 115V
- ◆ 15' power cord

SPOP8500

- ◆ 8500 GPH @ 5' TDH
- ◆ 22' shut-off head
- ◆ 363W
- ◆ 2" FNPT discharge
- ◆ Handles 1/8" solids
- ◆ 115V
- ◆ 15' power cord



Product Code	Description	Specification
SPOP3500	SurePro Energy Saver Out of Pond Pump	3500 GPH @ 5' TDH
SPOP4500	SurePro Energy Saver Out of Pond Pump	4500 GPH @ 5' TDH
SPOP5500	SurePro Energy Saver Out of Pond Pump	5500 GPH @ 5' TDH
SPOP8500	SurePro Energy Saver Out of Pond Pump	8500 GPH @ 5' TDH



LittleGIANT® Outdoor Living

We offer a full **decorative water** product line from the two great **brands** you know and **trust**

SUREPRO™



SCAN TO
LEARN MORE!

www.lg-outdoor.com

PRIMING POTS, DEBRIS TRAPS



SPPT2

Our 2" priming pot/debris trap is designed specifically for the water gardening industry. It features a camber lock lid with excellent flow through capabilities. Specially designed basket improves flow while keeping harmful debris such as string algae out of the pump.



- ◆ Strong glass-filled thermoplastic housing for long life
- ◆ High strength see through lid
- ◆ Best flow characteristics
- ◆ Quick-connect 2" union included
- ◆ Drain plug for winterizing
- ◆ Specially designed debris basket for maximum flow
- ◆ Comes with adaptor for use with most water garden pumps
- ◆ Flow range up to 6,000 GPH
- ◆ SPPT2 Dimensions: width = 6", height = 10"

SPPT3

The 3" priming pot/debris trap is specifically designed for the water gardening industry. With the 550 cubic inch capacity, it is designed for high flow applications. The loss of flow through the pump is minimal via the 3" inlet as well as the oversized capacity.



- ◆ Strong glass-filled thermoplastic housing
- ◆ Drain plug for winterization
- ◆ Adjustable feet to match with any pump height
- ◆ Quick-connect 3" union included
- ◆ Best flow of any priming pot/debris trap available
- ◆ Flow rates up to 13,000 GPH
- ◆ Keep harmful debris such as string algae out of pump
- ◆ SPPT3 Dimensions: width = 8.5", height = 18"

PLASTIC SUCTION STRAINERS

Product Code	Description
SPPSS10	SurePro Plastic Suction Strainer 1"
SPPSS15	SurePro Plastic Suction Strainer 1 1/2"
SPPSS20	SurePro Plastic Suction Strainer 2"
SPPSS30	SurePro Plastic Suction Strainer 3"



SUREPRO PRESSURE FILTERS



BIOLOGICAL BEAD FILTERS & ACCESSORIES

This pond and water feature filter is a pressure side system, designed to filter out small debris. It is designed to be used with energy efficient pumps. Comes with specially designed start-up bacteria. These units are designed for new applications or to retrofit existing ones.

- ◆ Works with low-amp pumps
- ◆ Easy to clean backwash feature
- ◆ Backwashing pressure filter may be placed anywhere on the discharge of the pump (perfect for retrofitting existing pond)
- ◆ Valve can be hidden in an artificial rock or valve box
- ◆ Bio bead media is designed for use with Koi and goldfish ponds
- ◆ Pressure gauge to indicate when to backwash

SPBF1000

- ◆ 1.5" valve
- ◆ For any pond or water feature up to 1000 gals.
- ◆ Dimensions: width = 19", height = 27"



SPBF2000

- ◆ 1.5" valve
- ◆ For any pond or water feature up to 2000 gals.
- ◆ Dimensions: width = 16", height = 32"



SPBF4000

- ◆ 2" valve
- ◆ For any pond or water feature up to 4000 gals.
- ◆ Dimensions: width = 19", height = 36"




SPBF6000

- ◆ 2" valve
- ◆ For any pond or water feature up to 6000 gals.
- ◆ Dimensions: width = 24", height = 43"



Product Code	Description
SPBF1000	1.5" valve, 1,000 gal.
SPBF2000	1.5" valve, 2,000 gal.
SPBF4000	2" valve, 4,000 gal.
SPBF6000	2" valve, 6,000 gal.

EXPLORE THE WORLD OF WATER FEATURES



DISCOVER ATLANTIC'S PREMIERE WATER GARDENING PRODUCTS

From all-in-one kits for easy installation to lighting accessories to enjoy your water feature deep into the evening. Explore our full line of Formal Spillways, SOL LED Lighting, TidalWave pumps and more.

- Atlantic Water Gardens products are available at all Horizon locations
- Atlantic offers online water gardening education, Atlantic Water Gardens University -- Visit AWGU under the tools section of our website



DISCOVER THE DIFFERENCE

Phone: 1.877.80PONDS | Fax: 330.274.8790 | info@atlanticwatergardens.com | www.atlanticwatergardens.com



Waterscapes
By Atlantic

L SERIES PUMP

TidalWave L-Series are axial flow pumps, specially designed to deliver high volumes through large diameter plumbing to relatively low heights. Under 10' of head, the low power consumption of these 3" outlet pumps can't be beat for your high flow applications. Built with the same robust cast iron and stainless steel construction as our A-Series, Atlantic's L-Series pumps will deliver for years.

Features

- ◆ Cast iron vortex impeller
- ◆ Double silicon carbide mechanical seals
- ◆ Dual drive bearings
- ◆ Auto-cut thermal protection
- ◆ 30' power cord
- ◆ 2-year warranty



CE
L-305

MODEL L-305

Volts:	115	Motor:	1/2 HP
Watts:	710	Amps:	6.4
Weight:	60 lbs.	Outlet:	3" MPT
Dimensions:	9"L x 9"W x 19.25"H		

MODEL L-310

Volts:	115	Motor:	1 HP
Watts:	1105	Amps:	10
Weight:	65 lbs.	Outlet:	3" MPT
Dimensions:	9"L x 9"W x 19.25"H		

* Wattage is calculated @ BEP using the following formula
(Volts x Amps x PF = Watts).

Model #	Watts	Max	5'	10'	15'	20'	25'	30'	35'	40'	45'	50'	55'	60'
L-305	710	--	10380	7380	3960									
L-310	1105	--	13500	10560	7380	3240								

*Operating pumps outside of the recommended range may cause bearing damage and premature failure.

Recommended Operating Range Best Efficiency Point Do Not Operate Range

Waterscapes
By Atlantic

A SERIES PUMP

TidalWave A-Series are manufactured from cast iron and stainless steel with precision motors and thermal overload protection. These professional-grade direct drive pumps are engineered for demanding high volume applications and perform where most cannot.

Features

- ◆ Cast iron vortex impeller
- ◆ Double silicon carbide mechanical seals
- ◆ Dual drive bearings
- ◆ Auto-cut thermal protection
- ◆ 30' power cord
- ◆ 2-year warranty

MODEL A-31

Volts:	115	Motor:	1 HP
Watts:	1160	Amps:	10
Weight:	48 lbs.	Outlet:	3" MPT
Dimensions:	11"L x 7"W x 18"H		

* Wattage is calculated @ BEP using the following formula (Volts x Amps x PF = Watts).

Model #	Watts	Max	5'	10'	15'	20'	25'	30'	35'	40'	45'	50'	55'	60'
A-05	645	--	3165	2840	2500	2155	1875	1455	935	320				
A-05L	725	--	5040	4320	3600	2820	1920	840						
A-21	1060	--	5810	5325	4824	4335	3770	3140	2400	1530	540			
A-31	1160	--	9300	8150	6830	5535	4120	2535	625					
A-32	2055	--	12000	11040	10440	9780	9000	8280	7560	6780	5580	4920	3890	

*Operating pumps outside of the recommended range may cause bearing damage and premature failure.

Recommended Operating Range Best Efficiency Point Do Not Operate Range



Volts:	230	Motor:	2 HP
Watts:	2055	Amps:	9.4
Weight:	95 lbs.	Outlet:	3" FIPT
Dimensions:	15"L x 8.5"W x 23"H		

Outdoor Living

Waterscapes
By Atlantic

SH SERIES PUMP

A mainstay of the Water Garden Industry, TidalWave SH-Series Pumps have proven to be one of the most dependable and energy-efficient composite direct drives available. With true solids handling capacities of up to 1½" and stable base geometry, these value-packed pumps excel under the most rigorous conditions..

Features

- ◆ Non-corrosive and handles solids
- ◆ Oil-Free design
- ◆ Vortex Impeller
- ◆ Overload and thermal protection
- ◆ 16' power cord
- ◆ 2-year warranty



WATER FEATURES – PUMPS (CONT.)

* Wattage is calculated @ BEP using the following formula (Volts x Amps x PF = Watts).

Model #	Watts	Max	5'	10'	15'	20'	25'	30'	35'
SH1450	240	1450	1170	650					
SH2050	320	2050	1700	1130	235				
SH3600	575	3600	3245	2750	2090	1210			
SH5000	950	5000	4350	3620	2800	1875	825		
SH6500	1000	6500	5710	4875	4000	3080	2110	1085	

*Operating pumps outside of the recommended range may cause bearing damage and premature failure.

Recommended Operating Range Best Efficiency Point Do Not Operate Range

SH3600 Model Specifications

Volts:	115	Outlet:	1.25" FIPT w/1.5" FIPT elbow
Amps:	5.5	Dimensions:	6"L x 9"W x 14"H
Watts:	575		

SH5000 Model Specifications

Volts:	115	Outlet:	1.5" FIPT w/1.5" FIPT elbow
Amps:	9	Dimensions:	9.5"L x 12"W x 15.75"H
Watts:	950		

SH6500 Model Specifications

Volts:	115	Outlet:	1.5" FIPT w/1.5" FIPT elbow
Amps:	9.5	Dimensions:	9.5"L x 12"W x 15.75"H
Watts:	1000		

IONIZERS

TRITON IONIZER

The Triton Ionizer's modular design is at the cutting edge of innovation, featuring tool-less, seamless integration with our award-winning Triton Check Valve! Safe for animals and plants and unaffected by sunlight and heat, this mineralized water maintains a residual ability to treat organics, greatly reducing the need for chemical treatments.

HOW IT WORKS

The Triton Ionizer utilizes the same union fittings and adapters as the Triton Check Valve, so connecting the Ionizer above or below the Check Valve takes only seconds. Periodic replacement of electrodes is just as simple. Instead of the whole assembly, only the electrodes are changed, again without needing tools. It doesn't get any simpler or better designed than this!



Features

- ◆ Safe for fish and plants
- ◆ Low maintenance
- ◆ Clears water without the use of harsh chemicals
- ◆ Level of mineralization is controlled by the LED panel
- ◆ Treats ponds up to 25,000 gallons
- ◆ Easily installed in any new or existing water feature
- ◆ Electrodes are easily replaced without tools
- ◆ 1-year warranty

TRITON IONIZER REPLACEMENT ANODE

Part Number: TRION2-RA

MDFH1020 Model Specifications

Description:	Electronic Water Clarifier
Application:	Pond / Pond-free / Fountain
Input Voltage:	12 volt AC
Watts:	2
Inlet/Outlet:	2" Sch 40 PVC
For Use With:	1000 – 2000 gph MD pumps
Includes:	Outdoor transformer and copper test strips



COLOR CHANGING COLORFALLS

Atlantic's Color Changing Colorfalls add a whole new dimension to Formal Spillways. The modular body style offers easier maintenance, with a removable back for easy access and side plumbing ports. A more generous weir opening resists clogging and creates a thicker, fuller sheer for extra color and less wind deflection. The innovative modular design with easy to install threaded couplings makes connecting any number of falls together a snap! The LED light bar offers 48 vibrant color options and 16 patterns via remote control.

Colorfalls Features

- 1) Larger weir opening produces a thicker sheer, less splash, more color and less chance of clogging
- 2) Redesigned supports eliminate splitting of the water sheer and increase load capacity
- 3) 1½" FIPT side and back plumbing options for maximum versatility
- 4) Includes (2) 1½" plugs for unused plumbing inlets
- 5) Self-draining body for easy winterization
- 6) Removable baffle for easy cleaning and servicing
- 7) Color Changing LED light bar that is accessible from the rear of the unit
- 8) Removable back plate provides unparalleled access to the interior and light bar for routine maintenance
- 9) Includes threaded adapter for connecting multiple Color Changing Colorfalls


CC06 Model Specifications

Description:	6" Color Changing Colorfalls
Flow Rate:	600 gph
Input Voltage:	12 volt DC
Watts:	3.5 Variable
Inlet:	1.5" FIPT
Dimensions:	6"W x 8"D x 3.5"H


Color Changing Features

- ◆ 5" lip extension
- ◆ 12 volt single control module with weather resistant outdoor enclosure & remote control
- ◆ 20' power cord
- ◆ 1-year warranty

12" Color Changing



24" Color Changing



CC12 Model Specifications

Description:	12" Color Changing Colorfalls
Flow Rate:	1200 gph
Input Voltage:	12 volt DC
Watts:	7 Variable
Inlet:	1.5" FIPT
Dimensions:	12"W x 8"D x 3.5"H

Stainless Steel Scuppers

Atlantic's newest entry to the Formal Spillways category, our Stainless Steel Scuppers bring a polished, gleaming dimension to our spillway line. Constructed of durable 304 stainless steel and available in the same sizes as our popular Colorfalls, these sleek modern Scuppers put a sharp, fresh shine on your formal water feature project.



12" Scupper

SS12 Model Specifications


Description:	12" Stainless Steel Scupper
Flow Rate:	1200 gph
Inlet:	1.5" FIPT
Dimensions:	12"W x 8.5"D x 4"H

Features

- ◆ 1) Larger 5" lip extension
- ◆ Fully welded enclosure
- ◆ 304 Stainless steel
- ◆ 1-year warranty



Scupper Inlet



24" Scupper

SS24 Model Specifications

Description:	24" Stainless Steel Scupper
Flow Rate:	2400 gph
Inlet:	1.5" FIPT
Dimensions:	24"W x 8.5"D x 4"H

Outdoor Living

WATERFALLS (CONT.)

Waterscapes
By Atlantic

BF1600

OASIS FilterFalls Features

1. Sturdy top grate and support bar allow natural rock camouflage
2. Media bag for additional biological filtration
3. Dual Bio-Tech filter mats for biological filtration
4. Sturdy bottom grate supports filter media
5. Rolled upper rim provides clean lines and incredible strength
6. One-piece liner attachment flange
7. Heavy-duty 1½" FIPT bulkhead

BF1600 Model Specifications

Waterfall Width:	16" Spillway
Dimensions:	21.5W x 19.5D x 17.75H
Pump Flow Range:	1000 – 3900 gph
Bulkhead:	1.5"
Pond Volume:	up to 250 gallons
Match to Skimmer:	PS3900



Model BF1600 shown

SP1900 and SP 2600

featuring deep plumbing channels on top of the basins, easy access pump chambers and external flow adjustment for convenient installation and maintenance. Now they're even better, with new internal buttressing cones for greater rigidity. Count on Atlantic to keep on performing!

OASIS FilterFalls Features

1. Sturdy top grate and support bar allow natural rock camouflage
2. Media bag for additional biological filtration
3. Dual Bio-Tech filter mats for biological filtration
4. Sturdy bottom grate supports filter media
5. Rolled upper rim provides clean lines and incredible strength
6. One-piece liner attachment flange
7. Heavy-duty 1½" FIPT bulkhead

SP1900 Model Specifications

Dimensions:	20.5W x 17D x 10.25H
Waterfall Width:	19"
Bulkhead:	1.5"
Max Pump Flow:	4000 gph
Bulkhead:	2" FIPT

SP2600 Model Specifications


Dimensions:	27.5W x 17D x 10.25H
Waterfall Width:	26"
Bulkhead:	1.5"
Max Pump Flow:	6000 gph
Bulkhead:	2" FIPT



SP1900



SP2600



Waterscapes
By Atlantic

Add another dimension to your water garden with Atlantic's Fountain Heads. Compatible with all of Atlantic's Mag Drive Pumps, these versatile Fountain Heads pivot to make leveling easy, telescope to adjustable heights and feature four different spray patterns to choose from..





MDFH2575 Model Specifications

Description:	Telescoping Fountain Head
Min Height:	12"
Max Height:	18"
Inlet:	3/4" FITP
Outlet:	1/2" insert
For Use With:	250 – 750 gph MD pumps
Includes:	Telescoping diverter w/4 interchangeable fountain heads

MDFH1020 Model Specifications

Description:	Telescoping Fountain Head
Min Height:	15"
Max Height:	22"
Inlet:	1" FITP
Outlet:	1" MIPT
For Use With:	1000 – 2000 gph MD pumps
Includes:	Telescoping diverter w/4 interchangeable fountain heads



Outdoor Living

Waterscapes
By Atlantic

FTN CC24 and FTN CC32

During the day the three sizes create the welcome sights and sounds of dancing water, bubbling up and cascading down their sides – but in the dark, they come alive with light! Working on the same technology as our Color Changing Colorfalls, these vases radiate in 48 different colors, or in 16 different pre-programmed patterns, with speed and intensity regulated by Remote Control.

Features

- ◆ Color changing LED light ring
- ◆ Remote control and control module
- ◆ Integrated anchor base for increased stability
- ◆ Durable rotomolded polyethylene construction
- ◆ Simulated granite finish
- ◆ Sold individually or as a 3-piece kit
- ◆ Each color changing vase includes LED light ring, SOL control module and remote

FTNPP32



FTNPP32 Model Specifications

Description:	Fiberglass Pebble Pot
Inlet:	.75 insert fitting
Dimensions:	18"W x 32"H
For Use With:	FB3200 Basin & F400 pump

FTN CCV24 Model Specifications

Description:	Color Changing Vase
Inlet:	.75" PVC pipe
Dimensions:	12"W x 24"H
For Use With:	FB3200 Basin, FBKIT1 & FP300 pump

FTN CCV32 Model Specifications

Description:	Color Changing Vase
Inlet:	.75" PVC pipe
Dimensions:	14"W x 32"H
For Use With:	FB3200 Basin, FBKIT1 & FP400 pump

Patent Pending

FOUNTAIN BASINS

FB3200

When they were introduced, Atlantic Fountain Basins were already the strongest and best-designed on the market, featuring deep plumbing channels on top of the basins, easy access pump chambers and external flow adjustment for convenient installation and maintenance. Now they're even better, with new internal buttressing cones for greater rigidity. Count on Atlantic to keep on performing!



PRO Series Fountain Basin Features

1. One-piece construction provides exceptional strength.
2. Built-in channels simplify installation, allowing the plumbing to be run on top of the basin.
3. Seven molded cones support the top panel.
4. Recessed pocket accepts the Triton 3-Way Diverter. Adjusting the water flow to multiple pieces has never been easier.
5. Recessed 1 1/2" conduit recesses allow for clean installation in surrounding masonry without notching
6. Flat panel for optional AF1000 Auto Fill installation

FB3200 Model Specifications

Dimensions:	32"W x 13"H
Max Pump Flow:	2000 gph
Plumbing Size:	(3) .75" or (1) 1" hose
Capacity:	32 Gallons
Supports Up To:	400 lbs.



Model FB-4600 shown

INTERNAL CONE SUPPORT SYSTEM



CFBASINKIT12 and CFBASINKIT24

Atlantic Basin Kits are designed to fit all our formal spillways perfectly. Whether you're adding the shimmering nighttime enchantment of a Classic or Color Changing Colorfalls or the elegant touch of class of the Stainless Steel Scupper, our Basin Kits provide everything you need to complete the installation, from the reservoir to the plumbing to the pump, with double filtration, tubing, fittings, anti-splash mat and even an Automatic Fill Valve.

Basin Kits Include

- ◆ Colorfalls Basin & TW2 Pump
- ◆ 1½" x 10' Flexible PVC Pipe
- ◆ Splash Mat
- ◆ AF1000 Auto Fill
- ◆ Complete Installation Kit including pump discharge, flow valve, spray glue and thread sealant

CFBASINKIT12 Model Specifications

Description:	Complete Basin Kit
For Use With:	All 12" Spillways
Dimensions:	20"W x 20"D x 16"H
Includes:	CFBASIN12 and TW 1200 pump

CFBASINKIT24 Model Specifications

Description:	Complete Basin Kit
For Use With:	All 24" Spillways
Dimensions:	44"W x 22"D x 16"H
Includes:	CFBASIN24 and TW 2400 pump



12" Basin Kit

24" Basin Kit

PUMP VAULTS

PV1700

Atlantic's heavy-duty one-piece rotomolded Pump Vaults offer all the strength and versatility you need for your Pond-free projects. Liberal volumes and copious flow capacities handle multiple pump configurations and larger pumps, while strong, tightly-fitting covers and generous openings provide easy pump and pipe access.



PV1700 Model Specifications

Dimensions:	17"W x 12"D x 22"H
Max Pump Flow:	3900 gph
Opening:	10"



1. Inset lid keeps gravel from falling into the vault
2. Pump discharge step fittings for 1½" & 2" pipe provided on both sides of the vault
3. Flat front panel installs tight against Eco-Blox for a compact basin
4. Recessed pockets accept Triton 3-Way Diverter for use with the Eco-Rise
5. Flat panel for 1½" pipe for use with the Eco-Rise

Outdoor Living

Waterscapes
By Atlantic

DIVERTER KITS

FBKIT1



FBKIT1 Model Specifications

For Use With: FP200 – 500 & MD250 – 750

- ◆ Single ball valve
- ◆ 6' of .75" diameter kink-free hose
- ◆ (1) standpipe sealant strip
- ◆ .75" insert x .75" socket fitting
- ◆ 1.5" cord stopper for conduit sleeve

*.75" PVC standpipe & pump not included

FBKIT3



FBKIT3 Model Specifications

For Use With: FP1200 – 2400 & MD1000 – 2000

- ◆ Triton 3-Way Diverter
- ◆ 20' of .75" diameter kink-free hose
- ◆ (3) standpipe sealant strips
- ◆ (3) .75" insert x .75" socket fittings
- ◆ (2) 1.5" cord stoppers for conduit sleeve

*.75" PVC standpipe & pump not included

TR3WAY

The Triton 3-Way Diverter is the only manifold designed exclusively for pond-free fountain installations. The 1½" inlet allows unrestricted flow into the manifold, delivering the maximum possible volume to all three of the 3/4" outlets. True 'ball' style valves with removable handles enable independent flow adjustment of each outlet. The compact design makes it a perfect fit for installation in all Pump Vaults and Fountain Basins.

TR3WAY Model Specifications

Dimensions: 5.75"L x 4.5"W x 2.875"H

Inlet: 1.5" FIPT

Outlet: (3) .75" Insert


Includes: (2) removable "T" handles





ECO-BLOX

Atlantic's proprietary Eco-Blox water matrix saves you time and money on all your rainwater harvesting, stormwater management and pond-free installations. With 96% void space, Eco-Blox reservoirs store large volumes of water easily and economically. Underground and out of sight, their enormous strength allows for landscaping right over the reservoir.



PV1700 Model Specifications

Dimensions:	27"L x 16"W x 17.5"H
Capacity:	31.5 Gallons
Application:	Pond-free / Fountain / Rain Harvesting

Eco-Blox water matrices still hold 31.5 gallons of water but support even greater loads this year, with an all-new formulation that increases flexibility and ease of assembly even under the most adverse conditions, and provides greater comprehensive and point load strength for a lifetime of dependable service!

ECO-RISE

The extremely strong radial structure handles the weight of heavier statuary, vases and columns while providing a broad stable base over Eco-Blox reservoirs. The versatility of the Eco-Rise used in conjunction with Eco-Blox, PV1700 Pump Vault and Triton 3-Way Diverter allows for multiple features in any configuration above odd basin shapes, while keeping plumbing and flow adjustment topside for easy access.


ECORISE20 Model Specifications

Dimensions:	20"L x 20"W x 3"H
Plumbing Size:	.75" to 1.5"
Max Load:	3000 lbs.



Typical Fountain ECO-RISE Installation

PV1700 Pump Vault shown with 3-Way Diverter installed for use with the Eco-Rise and Eco-Blox. Add a second pump and a second 3-Way Diverter to control up to six water features from a single PV1700 Vault.



Outdoor Living

Waterscapes
By Atlantic

PS7000 and PS15000

Atlantic's Pond Skimmers offer just what you need for all of your pond projects. With ample pre-filtration options, auto fill capacity, complete freedom in plumbing location, multiple pump capability and remarkable strength and rigidity, these versatile components allow for every style and preference!

PRO Series Skimmer Features

1. Sturdy removable top lid supports natural rock camouflage and foot traffic
2. Heavy-duty brush panel provides maximum surface area for mechanical filtration
3. Heavy-duty stainless steel framed trap net for catching large debris
4. Rolled upper rim provides clean lines and great strength
5. Super Flow weir door for maximum surface cleaning
6. High-density polyethylene shell for the ultimate in durability



Model PS7000 shown

SKIMMERS

PS7000 Model Specifications

Weir Width:	9"
Internal Water Depth:	17.5"
Dimensions:	25"W x 30"D x 24"H
Max Pump Flow:	7000 Gallons
Sq. Ft. Rating:	900 lbs.
Filtering:	Net, Brush panel
Match to Filter Falls:	BF2600

PS15000 Model Specifications

Weir Width:	14"
Internal Water Depth:	24.5"
Dimensions:	28"W x 33"D x 31"H
Max Pump Flow:	15,000 Gallons
Sq. Ft. Rating:	1400 lbs.
Filtering:	Net, Brush panel
Match to Filter Falls:	BF3800



PS7000



PS15000

SUREPRO MISCELLANEOUS

PLANT BASKETS

- ◆ Allows soil to be placed in basket without lining
- ◆ Allows water to reach root system
- ◆ Plant and fish friendly
- ◆ Prevents soil from eroding away
- ◆ 9" diameter round or 12" square



Product Code	Description
SPPBR	SurePro Plant Basket 9" Round
SPPBS	SurePro Plant Basket 12" Square

EPDM LINER



FIRESTONE POND GARD EPDM LINER

PondGard membrane is based on EPDM synthetic rubber, a highly flexible stable waterproofing membrane. PondGard is specially formulated to be safe for exposure to fish and plant life in decorative ponds. It can easily be shaped to fit the unique contours of any pond. PondGard shows outstanding resistance to the harmful effects of ultraviolet radiation (UV), ozone and other environmental conditions. It requires little or no regular maintenance once installed.



Product Code	Description
PL5100	5' X 100" EPDM Liner
PL10100	10' X 100" EPDM Liner
PL15100	15' X 100" EPDM Liner
PL20100	20' X 100" EPDM Liner
PL25100	25' X 100" EPDM Liner
PL30100	30' X 100" EPDM Liner
PL40100	40' X 100" EPDM Liner
PL50100	50' X 100" EPDM Liner
PL550	5' X 50' EPDM Liner
PL1550	15' X 50' EPDM Liner
PL1050	10' X 50' EPDM Liner
PL2050	20' X 50' EPDM Liner
PL2550	25' X 50' EPDM Liner
PL3050	30' X 50' EPDM Liner
PL4050	40' X 50' EPDM Liner
PL5050	50' X 50' EPDM Liner


MISCELLANEOUS - ACCESSORIES



W56RAC1693

Firestone QuickSeam Cover Strip, 6" X 25'

- ◆ 6" wide cover tape for seaming EPDM rubber liner. Sticky on one side



W563582023

Firestone QuickSeam Silicone Roller, 1 5/16"



W563582045

Firestone QuickSeam Scrubber Kit

- ◆ Includes 30 scrub pads and four holders that allow the installer to apply QuickPrime Plus or Seam Prep when seaming two sections of PondGard EPDM liner



W563587112


Firestone QuickPrime Plus, 1 gal. (W563587041) or qt.

- ◆ Designed to clean and prime Firestone EPDM prior to the application of the QuickSeam products



W56RAC1646

Firestone QuickSeam Corner Flashing, 8 1/2" diameter



Outdoor Living

UNDERWATER LIGHTING



SurePro Underwater Lighting

With the right lighting, water gardens can be enjoyed long after the sun sets. Light adds new dimension to landscapes and waterscapes as the white or colored hues play against the ripples of the water, magnify the pleasing effect of fountains or underscore the beauty of statues and other forms of garden art.

SPLEDK

- ◆ Submersible LED Light and Transformer kit includes one LED light with free standing support, fountain nozzle attachments in two different lengths and transformer
- ◆ Contains one LED light with 11 different pre-programmed lighting Options



Product Code	Description
SPLEDK	SurePro Underwater Kit w/ Transformer, Fixture & LED Lamp

SPLEDF

- ◆ LED Light with stand and nozzle attachments. LED light with 20' power cord connects to 120V transformer
- ◆ Comes pre-programmed with 11 lighting options ranging from brilliant red to a continuous transition of soft color, you can easily reflect any mood



Product Code	Description
SPLEDF	SurePro Underwater Fixture w/ LED Lamp

SPLEDL

- ◆ LED Replacement Bulb is programmed with 11 different modes — choose from Red, Yellow, Green, Aqua, Blue, Purple, White, Celebration mode and three time-changing Spectrum mode options. Each easily installed fixture features push-in, MR16-style terminal power pins



Product Code	Description
SPLEDL	SurePro LED Replacement Lamp

SPLVK

- ◆ Fully submersible 12V light
- ◆ 20W MR16 halogen lamp
- ◆ Includes one each colored lens (Yellow, Blue, Red and Green)
- ◆ Weather-proof, 120V transformer with on-off timer
- ◆ Powers up to three 20W lights



Product Code	Description
SPLVK	SurePro Underwater Kit w/ Transformer, Fixture & MR-16 Lamp

SPLVF

- ◆ Fully submersible 12V light with 20W MR16 halogen lamp
- ◆ Includes one each colored lens (Yellow, Blue, Red and Green)



Product Code	Description
SPLVF	SurePro Underwater Fixture w/ MR-16 Lamp

POND ACCESSORIES

PIPE

Product Code	Description
FLEX0550	1/2" flex PVC hose, 50'
FLEX07550	3/4" flex PVC hose, 50'
FLEX150	1" flex PVC hose, 50'
FLEX12550	1 1/4" flex PVC hose, 50'
FLEX1550	1 1/2" flex PVC hose, 50'
FLEX250	2" flex PVC hose, 50'
FLEX350	3" flex PVC hose, 50'

For complete information on waterscaping; from how to install it to how to sell it, visit horizononline.com.



Liquid Water Clarifiers

MICROBE-LIFT/PL

- ◆ Use any time your pond water is not as clear as you'd like, the temperature is over 45°F (8°C), or there is sediment buildup on the bottom of your pond or your pond is not cycling
- ◆ Balances your pond's ecosystem by establishing all natural biological processes required to: keep water clear and clean; reduce or eliminate organic sludge buildup; and seed your filter
- ◆ Does the work of three to four competitive products
- ◆ The only pond product with photosynthetic microorganisms
- ◆ Safe if pets drink out of a pond treated with PL



BARLEY STRAW CONCENTRATED EXTRACT (CBSE)

- ◆ Start in the spring before water temperatures reach 50°F (10°C) and continue throughout the year to provide water clarity when ML/PL alone does not provide the desired results
- ◆ Preferred by pond owners with bottom drains since it leaves no residue
- ◆ Provides many of the same benefits as ML/BSP but without the peat so there is no residue
- ◆ Contain pre-digested barley that release these same compounds within one to five days

ALGAWAY 60

- ◆ Chemical algae eliminator formulated for decorative ponds and fountains, irrigation ponds, water hazards and retention ponds
- ◆ Eliminates most planktonic and filamentous algae quickly and efficiently and there's no phytotoxicity so water is safe for irrigation, turf and shrubs
- ◆ Is a highly concentrate (60% active ingredient) EPA registered algicide



ALGAWAY 5.4

- ◆ Algaecide for ponds
- ◆ Can be applied to areas that contain fish and plants
- ◆ 5.4% active ingredient
- ◆ For use in self-contained ornamental ponds and fountains without overflow

Product Code	Description
10PBLXG	Microbe-Lift Pro Blend Liquid gal.
10PBLXQ	Microbe-Lift Pro Blend Liquid qt.
MLCBSE1L	Microbe-Lift Concentrate Barley Straw Ext 32 oz.
AAG60G	Microbe-Lift Algaway 60, 1 gal.
AAG60Q	Microbe-Lift Algaway 60, 32 oz.
ALGA16	Microbe Lift Algaway 5.4, 16 oz.
ALGAG	Microbe-Lift Algaway 5.4, 1 gal.

Dry Water Clarifiers

BSP (BARLEY STRAW PELLETS+)

- ◆ Start in the spring before water temperatures reach 50°F (10°C) and continue maintenance throughout the year
- ◆ To provide additional water clarity when MICROBE-LIFT/PL alone does not provide the desired degree of clarity
- ◆ Pellets sink to the bottom within minutes and dissolve quickly
- ◆ May turn pond water a tea-color for 10 to 14 days and does leave a residue from the peat



Product Code	Description
10BSPP2.2	Microbe-Lift Barley Straw Pellets
10BSPP4.4	Microbe-Lift Barley Straw Pellets

Specialty Bacteria & Enzyme Products

NITE-OUT II

- ◆ Use when the ammonia levels in your pond exceed 0.8 mg/L and the temperature is over 50°F (10°C), especially useful when starting up a pond and when nitrite buildup is observed
- ◆ Quickly establishes the necessary populations required to efficiently cycle nitrogen compounds in the pond, i.e. oxidize ammonia to nitrite, and nitrite to nitrate
- ◆ Acts within a day or two to lower ammonia nitrogen and nitrite nitrogen levels naturally



SA (SLUDGE AWAY)

- ◆ Use any time there is excessive non-cellulosic organic sludge buildup in the bottom of the pond, especially rock bottom ponds
- ◆ Helps solubilize organic sludges making them more readily available for biodegradation
- ◆ Has been shown to break down up to 3" of sludge in as little as four weeks
- ◆ Should be used with Microbe-Lift/PL



Product Code	Description
NITE32	Microbe-Lift Niteout II Nitrifying Bacteria 32 oz.
MLXSAG	Microbe-Lift Sludge Away gal.
MLXSAQ	Microbe-Lift Sludge Away qt.

Outdoor Living

WATER TREATMENT (CONT.)

Chemical Water Treatments

FLOCCULANT PLUS

- ◆ To clear cloudy water and improve filtration
- ◆ A proprietary water clarifier formulation used to attract and coagulate suspended solids in the pond water
- ◆ After use, particles in the water settle to the bottom of the pond and/or filter out through the filter system



DEFOAMER

- ◆ Use when unsightly foaming is persistent in ponds and fountain of all sizes
- ◆ Eliminates foam in seconds leaving pond water clean and clear by increasing surface tension of the water
- ◆ Foaming can indicate a heavy concentration of undissolved particulate organics



Product Code	Description
FPLUS16	Microbe-Lift Flocculant PLUS 16 oz.
FPLUS32	Microbe-Lift Flocculant PLUS 32 oz.
DFOAM16	Microbe-Lift Defoamer 16 oz.
DFOAM32	Microbe-Lift Defoamer 32 oz.

Filter Products

SUPER START BEAD FILTER BACTERIA

- ◆ Use when starting up a bead filter or after maintenance or rebedding of the filter
- ◆ Provides population that quickly colonizes beads to provide rapid startup of bead filters
- ◆ Helps to stabilize overall process especially after maintenance
- ◆ Contains populations that are effective in producing biopolymers, glue-like substances, that aid in bacterial attachment and film formation



Product Code	Description
MLBFBQ	Microbe-Lift Bead Filter Bacteria 1 qt.

BiSafe Systems LLC GreenClean

BIOSAFE

- ◆ Works on contact to control algae in water gardens, ornamental ponds, fountains, and other water features
- ◆ Patented formula immediately begins fighting algae blooms, releasing vital oxygen into the water body as it biodegrades
- ◆ Ready-to-use




Product Code	Description
GREENCLEAN2	2lb. bottle algaeicide
GREENCLEAN8	8lb. bottle algaeicide
GREENCLEAN20	20lb. pail algaeicide



ECO-VENETIAN STONE™ COMBO

Its modular square and rectangular shapes and uniquely attractive cleft surface set it apart from other permeable pavement treatments. This texture resembles stone facing and invokes a more natural convention. The Eco-Venetian Stone™ larger scales lends itself to stately residential settings and more expansive commercial applications.

The unique Eco-Venetian™ joint profile allows surface water to infiltrate into the pavement and its sub-layers. With initial permeability average flow rates of over 100" per hour, the Eco-Venetian™ product, even with a clogging factor, will still meet the majority of current storm water management plans (SWMP).



Specifications:	
Giant — 3 1/8" Length: 9 3/16" Width: 9 3/16" Height: 3 1/8" Stones/Pallet: 80 Stones	Large Rectangle — 3 1/8" Length: 9 3/16" Width: 4 1/2" Height: 3 1/8" Stones/Pallet: 80 Stones
Square — 3 1/8" Length: 4 1/2" Width: 4 1/2" Height: 3 1/8" Stones/Pallet: 48 Stones	Med. Rectangle. — 3 1/8" Length: 6 13/16" Width: 4 1/2" Height: 3 1/8" Stones/Pallet: 96 Stones
Applications:	
Parking Lots Driveways Patios Entrance Areas Sidewalks	Terraces Garden Pathways Pool Decks Pedestrian Malls Roof Gardens

HOLLAND STONE

The renowned durability of interlocking pave stones, Holland Stone offers the old world charm of a simple paver shape. The rectangle shape can be installed in a number of fascinating patterns to produce simple or intricate designs.




Holland Stone is available in Standard, Parkway™ (non— chamfered edges), Provincial™ (smooth) and Heritage™ (tumbled) Series finishes.

Specifications:	
Holland Stone — 2 3/8" Length: 7 13/16" Width: 3 7/8" Height: 2 3/8" Stones/Pallet: 480 stones	Holland Stone — 3 1/8" Length: 7 13/16" Width: 3 7/8" Height: 3 1/8" Stones/Pallet: 384 stones
Applications:	
General Road Construction Parking Lots Gas Stations Driveways Patios Highway Ramps Highway Rest Areas Bridge Underpasses Entrance Areas Industrial Plants Industrial Yards Storage Depots	Loading Docks Flooring in Stables Sidewalks Terraces Garden Pathways Pool Decks Beach Promenades Pedestrian Malls Roof Gardens Street Medians

PLAZA STONE

This timeless paving stone offers a rich embossed surface for multiple applications. It has an array of stone shape options and is available in many colors.



The Plaza Stone comes with a non-tumbled finish which is shown here but is also available in the Plaza Stone Heritage or tumbled finish which will add additional texture to the stones finish.

Specifications:	
Large Rectangle — 2 3/8" Length: 8 3/16" Width: 5 7/16" Height: 2 3/8" Stones/Pallet: 300 stones	Large Rectangle — 3 1/8" Length: 8 3/16" Width: 5 7/16" Height: 3 1/8" Stones/Pallet: 240 stones
Plaza Stone — Square — 2 3/8" Length: 5 7/16" Width: 5 7/16" Height: 2 3/8" Stones/Pallet: 480 stones	Plaza Stone — Square — 3 1/8" Length: 5 7/16" Width: 5 7/16" Height: 3 1/8" Stones/Pallet: 384 stones
Giant — 2 3/8" Length: 10 15/16" Width: 8 3/16" Height: 2 3/8" Stones/Pallet: 160 stones	
Applications:	
General Road Construction Parking Lots Driveways Patios Bridge Underpasses Entrance Areas Flooring in Stables	Sidewalks Terraces Garden Pathways Pool Decks Pedestrian Malls Roof Gardens

Outdoor Living

PAVERS (CONT.)

VENETIAN STONE

The Venetian Stone™ product advent is the latest development in enhanced pavers. Its uniquely attractive cleft surface sets it apart from other pavement treatments.



This texture resembles old world charm and invokes a traditional convention. The Venetian Stone™ larger scales lends itself to stately residential settings and more expansive commercial applications. Its modular pattern equalizes the scale of any project and is fitting to most any architectural elements. The standard finish is shown but the tumbled finish or Heritage™ finish of the Venetian Stone also adds additional texture from our standard finish.

Specifications:	
Giant — 2 3/8"	Large Rectangle — 2 3/8"
Length: 11 3/4" Width: 11 3/4" Height: 2 3/8" Stones/Pallet: 120 stones	Length: 11 3/4" Width: 5 13/16" Height: 2 3/8" Stones/Pallet: 200 stones
Rectangle — 2 3/8"	
Length: 8 3/4" Width: 5 13/16" Height: 2 3/8" Stones/Pallet: 250 stones	
Applications:	
Driveways Patios Entrance Areas Sidewalks Terraces	Garden Pathways Pool Decks Pedestrian Malls Courtyards Plazas

VINTAGE STONE

The tumbled Vintage Stone™ Giant Heritage™ product mixture delivers scale, color, and modular design options for a unique pavement expression. The truly random pattern of Vintage Stone™ expands an infinite number of impression possibilities making it one of the most popular design tools for pavements today.



The tumbled Heritage™ texture and the Giant Vintage Stone™ open up the scale for more elegant designs.

Specifications:	
Vintage Stone™ Giant — 2 3/8"	Vintage™ Rectangle — 2 3/8"
Length: 8 3/4" Width: 8 3/4" Height: 2 3/8" Stones/Pallet: 200 stones	Length: 8 3/4" Width: 5 13/16" Height: 2 3/8" Stones/Pallet: 250 stones
Applications:	
Driveways Patios Entrance Areas Sidewalks Terraces	Garden Pathways Pool Decks Pedestrian Malls Courtyards Plazas

RETAINING WALLS



ANCHOR HAMPTON STONE® BEVELED


Anchor Hampton Stone® is perfect for wall projects up to 3' (900 mm) and higher with reinforcement. The Anchor Hampton Stone® features a natural appearance, is available in warm earth tones, and in a straight or bevel face.

Specifications:
Anchor Hampton Stone® Beveled
Length: 15 7/8" Width: 10" Height: 6" Stones/Pallet: 45 stones Face Ft./Pallet: 30 sq. ft.
Applications:
Terraced Gardens Landscaped Retaining Walls Geosynthetic Reinforced Tall Walls Erosion Control



ANCHOR HIGHLAND STONE

The Anchor Highland Stone® with it's rough—hewn exterior and patented rear lip system is now available in both 6" and 3" heights. Use these stones alone or mixed together to create natural stone beauty without sacrificing stability.



The Anchor Highland Stone® is a integral part of the 3" or 6" Combo retaining wall system. It combines earthen tones, rich textures and varied contours to make it a reliable alternative to natural stone walls. The stone-like, multi-colored face contributes to the impression of a natural rock wall.

Specifications:	
Anchor Highland Stone® Large	Anchor Highland Stone® Medium
Depth: 12" Width: 18" Height: 6" Stones/Pallet: 45 stones Face Ft./Pallet: 33 sq. ft.	Depth: 12" Width: 12" Height: 6" Stones/Pallet: 48 stones Face Ft./Pallet: 24 sq. ft.
Anchor Highland Stone® Small	
Depth: 12" Width: 6" Height: 6" Stones/Pallet: 80 stones Face Ft./Pallet: 20 sq. ft.	
Applications:	
Terraced Gardens Landscaped Retaining Walls Geosynthetic Reinforced Tall Walls Erosion Control	



ANCHOR HIGHLAND STONE FSW (FREE STANDING WALL)

The Anchor Highland Stone® Free Standing Wall is crafted with the same earthen colors and rough-hewn texture that made Anchor Highland Stone® a top choice for retaining walls.



It is offered in a straight or curved option. The Anchor Highland Stone® Free Standing Wall is our most versatile product yet.

Specifications:	
Anchor Highland 6" FSW Front Depth: 9" Width: 6" Height: 6" Stones/Pallet: 100 stones Face Ft./Pallet: 32 sq. ft.	Anchor Highland 6" FSW Back Depth: 9" Width: 4" Height: 6" Stones/Pallet: 100 stones Face Ft./Pallet: 32 sq. ft.
Anchor Highland 12" FSW Depth: 9" Width: 12" Height: 6" Stones/Pallet: 60 stones Face Ft./Pallet: 30 sq. ft.	Anchor Highland 18" FSW Front Depth: 9" Width: 18" Height: 6" Stones/Pallet: 40 stones Face Ft./Pallet: 30 sq. ft.
Anchor Highland 18" FSW Back Depth: 9" Width: 16" Height: 6" Stones/Pallet: 40 stones Face Ft./Pallet: 30 sq. ft.	
Applications:	
Seating Areas Borders	Pilasters Columns

RUMBLED™ WALL

Capturing the old world charm, Rumbled™ Wall by Pavestone Company invites history and tradition into the modular wall product offering. Available in square and rectangle shapes, simplicity and functionalism are combined. Dry stacked or mortar set Rumbled™ Wall is easily constructed and visually distinguishes itself from other retaining structures.



Specifications:	
Rumbled Wall Square Depth: 8" Width: 8" Height: 4" Stones/Pallet: 112 stones Face Ft./Pallet: 25 sq. ft.	Rumbled™ Wall Rectangle Depth: 8" Width: 16" Height: 4" Stones/Pallet: 70 stones Face Ft./Pallet: 31 sq. ft.
Applications:	
Landscape Walls Grill Enclosures Privacy Walls Columns	Benches Planters Fountains



Outdoor Living

PERMEABLE PAVERS


Horizon Distributors offers all of the commonly specified permeable paver systems including:



NDS TUFFTRACK® GRASSROAD PAVERS®

Permeable pavers designed for natural grass paved environments as an alternative solution to concrete, asphalt or similar surfaces.

- ◆ Composed of a series of cells that connect to form a grid system which provides a stable and continuous surface that can withstand significant structural loads
- ◆ Designed to transfer vehicle load to the paver base while preventing soil compaction within paver cells
- ◆ Allow for healthy turf growth in areas of high traffic
- ◆ Aesthetically pleasing and environmentally friendly
- ◆ Can be used to achieve LEED® credits in multiple categories




Product Code	Description
TT24	24" X 24" Tufftrack® Grassroad Pavers® Black 1/132 4.00 55GP

NDS EZ ROLL™ GRASS PAVERS

Plastic grass pavers that allow light to heavy vehicular traffic to drive over turf areas.

- ◆ Prevents soil compaction, allowing healthy root growth where grass can thrive
- ◆ Used to stabilize soil and allow turf to grow in areas that would traditionally have impervious hardscaping installed
- ◆ Can be used as a BMP for NPDES Phase II compliance
- ◆ Pre-assembled rolls for easy installation



Product Code	Description
EZ4X24	EZ Roll™ Grass Pavers, 4' X 24' roll, 96 sq. ft. total
EZ4X150	EZ Roll™ Grass Pavers, 4' X 150' roll, 600 sq. ft. total

RECOMMENDED INSTALLATIONS FOR NDS GRASS PAVERS

<ul style="list-style-type: none"> • Frequent usage • Heavy duty vehicles • Heavy usage where vehicle tires will be turned frequently • Can be used for light applications without a road base 	<ul style="list-style-type: none"> • Emergency access roads that do not have frequent usage • OK for heavy vehicles • Must always be installed on a road base, even with light applications
--	--

NDS EZ ROLL™ GRAVEL PAVERS

A load transfer paving system designed to be placed directly on a clean stone or sandy gravel base.



- ◆ Allows light to heavy vehicular traffic to travel over turf without damage
- ◆ Can be used for erosion control and help reduce or eliminate surface water runoff
- ◆ Includes a fabric covering that is heat bonded to the bottom surface and allows water to drain freely into sub grade
- ◆ Packaged in rolls that can be rolled out over the base materials, allowing for easy installation and savings on labor costs

Product Code	Description
GP4X150	EZ Roll™ Gravel Pavers, 4' X 150' roll
GP4X150G	EZ Roll™ Gravel Pavers, 4' X 150' roll
GP4X150R	EZ Roll™ Gravel Pavers, 4' X 150' roll
GP4X150T	EZ Roll™ Gravel Pavers, 4' X 150' roll
GPClip	EZ Roll™ Gravel Paver Clips
GPSTAKE	EZ Roll™ Gravel Paver Stake

RECOMMENDED APPLICATIONS FOR NDS GRAVEL PAVERS

<ul style="list-style-type: none"> • Golf cart paths • Residential driveways • Service roads • Parking lots • Jogging tracks • Overflow parking area • Bike paths • Roadway shoulders • RV and boat access/parking • Truck & cart wash-down areas 	<ul style="list-style-type: none"> • Fire lanes • Emergency vehicle access roads • Service vehicle utility roads • Truck maintenance and equipment yards • Construction entrance soil stabilization 	<ul style="list-style-type: none"> • Erosion control on slopes • Erosion control in swales
---	--	--




This Classic series pre-cut calibrated flagstone is conveniently packaged to allow simple installation.

- ◆ Flagstone can be thin-set over concrete or sand set on base.
- ◆ Less cutting leads to minimal waste
- ◆ Calibrated to a 1" thickness
- ◆ 1 pallet covers 205 Sq Ft



LAKELAND



GOLDEN FOSSIL



DRY HARVEST



HARVEST



PROMENADE

Product Code	Description
SPU-GF-CLAS-1	Golden Fossil Classic
SPU-SB-CLAS-1	Steel Blue Classic
SPU-HAR-CLAS-1	Harvest Classic
SPU-LAK-CLAS-1	Lakeland Classic
SPU-PRO-CLAS-1	Promenade Classic
SPU-CHA-CLAS-1	Charcoal Classic

Premium series flagstone is also available in a variety of colors and finishes together with our Heritage range of pavers and cobblestones. Ask your local Horizon dealer for details.

Outdoor Living

QUIKRETE

Concrete bonding adhesive permanently bonds new concrete, plaster, and stucco to existing concrete, plaster and stucco. Eliminates the need for roughing the surface before the application. Exceeds the performance of ASTM C 1059 Type I and II.



Use for:

- ◆ Bonding New Concrete to old Concrete
- ◆ Bonding applications on concrete overlays 1" or thicker

Waterproofing:

Hydraulic Water-Stop Cement is rapid setting, high strength repair material designed to plug leaks instantly in concrete and masonry. Sets in 3-5 minutes and can be used above and below grade. Designed to block running water or leaks in cracked masonry or concrete surfaces.



Veneer Stone Mortar:

Veneer Stone Mortar is a Portland cement and hydrate lime based mortar designed for veneer applications and tuck pointing of manufactured and natural stone.



Concrete Mix:

The original 4000 psi average compressive strength blend of Portland cement, sand, and gravel or stone. Just add water. Use for any general concrete work.



Product Code	Description
1150-47	Power-loc Joint Sand
1137-80	80# Veneerstone Mortar
1126-11	10# Hydraulic Water Stop
9902-10	10.1 Oz Construction Adhesive
9902-11	29 Oz Construction Adhesive
9902-01	1 Gal Concentrate Bonding Adhesive
8610-01	1 Gal Acrylic Fortifier
8670-06	1 Gal Oil Stain Remover
8675-33	1 Gal Efflorescence and Rust Remover
8650-05	5.5 Stucco Repair Tube
8640-15	5.5 Concrete Crack Seal
8601-14	Concrete and Asphalt Cleaner
9901-14	Quart Concrete Bonding Adhesive
8640-00	Quart Concrete Crack Seal
1100-10	10# Quikrete 4000 Concrete Mix
1102-10	10# Mortar Mix
1319-18	10 oz Stucco Color-Sage
1319-17	10 oz Stucco Color-Birch
1319-01	10 oz Stucco Color-Charcoal
1319-06	10 oz Stucco Color-Pewter
8730-02	10 oz Stucco Color-Mocha
1319-10	10 oz Stucco Color-Sandstone
1245-11	10# Anchoring Cement
1585-20	20# Fast Set Grout
8610-10	10 Oz Self Leveling Sealant
9800-01	1.5# Concrete Accelerator
8730-02	1 Gal Concrete Sealer Satin Finish
8800-05	1 Gal Water Proofing Sealer-Natural Look

**TURFGRO SELECT**

A 1.5" pile, polyethylene monofilament with thatch construction. Designed specifically for landscape application to enhance recovery.

Recommended Use: Light to moderate Traffic

Colors: Field Green/Olive Green or Field Green/ Lime Green

Features:

- ◆ Designed to truly replicate grass
- ◆ 1.5" blade height to achieve a natural appearance
- ◆ Uniquely formulated polyurethane coated backing provides greater seam strength and durability. Not water soluble
- ◆ Heat and frost resistant, UV stabilized
- ◆ No harmful environmental effects
- ◆ Non-flammable, ant-acid yarn resistant to chemical attack

Turf Characteristics	Manufactured Rolls	Particulate Infil
Pile/Face Weight: 50 oz.	Width: 15'	Type: Quality Infil
Pile Height: 1.5"	Length: 100 ft.	Weight: 1.5 – 2 lbs. per sq. ft.
Machine Gauge .5"	Ship Weight: 802 lbs.	Height: approx .5" to .75"
Thatch Color: Brown	Roll Diameter: 24"	Color: Green



Product Code	Description
TGP-53-1206	15' x 1' LT 2 Olive
TGP-53-1207	15' x 1' LT 2 Lime

TURFGRO ELITE

A 1.75" pile, polyethylene monofilament with thatch construction. Designed specifically for landscape application to enhance recovery.

Features:

- ◆ Designed to truly replicate grass
- ◆ 1.75" blade height to achieve a natural appearance
- ◆ Uniquely formulated polyurethane coated backing provides greater seam strength and durability. Not water soluble
- ◆ Heat and frost resistant, UV stabilized
- ◆ No harmful environmental effects
- ◆ Non-flammable, ant-acid yarn resistant to chemical attack

Turf Characteristics	Manufactured Rolls	Particulate Infil
Pile/Face Weight: 65 oz.	Width: 15'	Type: Quality Infil
Pile Height: 1.75"	Length: 100 ft.	Weight: 1 – 2 lbs. per sq. ft.
Machine Gauge .375"	Ship Weight: 959 lbs.	Height: approx .5" to .75"
Thatch Color: Brown	Roll Diameter: 24"	Color: Green

Recommended Use: Light to moderate Traffic

Colors: Field Green/Olive Green or Field Green/ Lime Green

Product Code	Description
TGP-53-1171	15' x 1' Linear Ft. Lime
TGP-53-1174	15' x 1' Linear Ft. Olive

TURFGRO ULTIMATE

A 1.875" pile, polyethylene monofilament with thatch construction. Designed specifically for landscape application to enhance recovery.

Recommended Use: Light to moderate Traffic

Colors: Field Green/Olive Green or Field Green/ Lime Green

Features:

- ◆ Designed to truly replicate grass
- ◆ 1.875" blade height to achieve a natural appearance
- ◆ Uniquely formulated polyurethane coated backing provides greater seam strength and durability. Not water soluble
- ◆ Heat and frost resistant, UV stabilized
- ◆ No harmful environmental effects
- ◆ Non-flammable, ant-acid yarn resistant to chemical attack

Turf Characteristics	Manufactured Rolls	Particulate Infil
Pile/Face Weight: 80 oz.	Width: 15'	Type: Quality Infil
Pile Height: 1.875"	Length: 100 ft.	Weight: 1 – 2 lbs. per sq. ft.
Machine Gauge .375"	Ship Weight: 1209 lbs.	Height: approx .5" to .75"
Thatch Color: Brown	Roll Diameter: 24"	Color: Green

ARTIFICIAL GRASS IS GREAT FOR PETS!

- ◆ Pet Hotels
- ◆ Dog Parks
- ◆ Pet Shows
- ◆ Dog Runs
- ◆ Backyards
- ◆ Animal Shelters
- ◆ Animal Hospitals
- ◆ Pet Training Areas
- ◆ And Much More!



This Product contains no detectable traces of lead or other RCRA hazardous waste heavy metals.

Product Code	Description
TGP-53-1169	15' x 1' Linear Ft. Lime
TGP-53-1173	15' x 1' Linear Ft. Olive

Outdoor Living

OUTDOOR KITCHEN ENCLOSURES


rtf systems™

Ready-To-Finish Outdoor Kitchen Systems

Ready-To-Finish Outdoor Kitchen System

The Ready-To-Finish Outdoor Kitchen System™ is the fastest, most efficient, and most profitable method for building outdoor kitchens. The modular cabinets will allow you to create completely customized designs and finish them with any veneer and countertop material you choose, and the adjustable frames will accommodate any grill and any accessory.

Because the cabinets assemble in a few hours, not days, building outdoor kitchens has never been easier. If you can operate a screw gun, then you can use the Ready-To-Finish Outdoor Kitchen System.™ **You will save time and make more money on every project!**



FEATURES & BENEFITS

Lightweight

Compared to concrete block construction, our system is as light as a feather. The RTF Outdoor Kitchen System™ weighs about 50 lbs. per linear ft.

Customizable



From the shape and size of the outdoor kitchen, to the veneer and countertops, even the appliances, The RTF Outdoor Kitchen System™ is designed to be completely customizable and universal - allowing you to design to your customers specifications.

Fast, Efficient, & Profitable



A screw gun, level, and a 4 in. grinder is all it takes to assemble and configure the RTF Outdoor Kitchen System™ cabinets. That means there's no mess to clean up, no lawn to repair, and no fence to put back up. It also means you'll make more money per job than with concrete block or any other system on the market!

FAST, EASY ASSEMBLY


STEP 1 - Cutouts



STEP 2 - Assembly




STEP 3 - Configuration





Standard Cabinet Selections



© Copyright Tejas Originals, LLC All Rights Reserved | rtf systems™ and Ready-To-Finish Outdoor Kitchen System™ is a Trademark of Tejas Originals, LLC

rtf systems™
 Ready-To-Finish Outdoor Kitchen Systems


"L" Shaped Kitchen With Bar

Custom designs using standard cabinets



rtf systems™ Cabinets:	
QTY:	Item:
1 ea.	RTF48-29-AC
1 ea.	RTF24-29-AC
1 ea.	RTF90c-29-CC
1 ea.	RTF36-29-RC
1 ea.	RTF36-29-AC
1 ea.	RTF90c-BKSP
2 ea.	RTF36-BKSP
4 ea.	RTF-Corbel

Finishing Materials:	
QTY:	Item:
120 sq. ft.	Veneer Material
44 sq. ft.	Countertop Material
13.5 sq. ft.	Bar-top Material




Finishing materials quantities are estimates and provided for illustration purposes only. The quantities listed will vary based on the type of material chosen and should be verified prior to ordering.




“U” Shaped Kitchen With Bar

Custom designs using standard cabinets



rtf systems™ Cabinets:	
QTY:	Item:
1 ea.	RTF48-29-AC
1 ea.	RTF24-29-AC
2 ea.	RTF90c-29-CC
1 ea.	RTF36-29-RC
1 ea.	RTF36-29-AC
1 ea.	RTF18-29-AC
1 ea.	RTF48-29-KC
2 ea.	RTF90c-BKSP
2 ea.	RTF36-BKSP
6 ea	RTF-Corbel

Finishing Materials:	
QTY:	Item:
168 sq. ft.	Veneer Material
68 sq. ft.	Countertop Material
18 sq. ft.	Bar-top Material




Finishing materials quantities are estimates and provided for illustration purposes only. The quantities listed will vary based on the type of material chosen and should be verified prior to ordering.

Outdoor Living

OUTDOOR KITCHEN DESIGNS (CONT.)


rtf systems™
 Ready-To-Finish Outdoor Kitchen Systems

Straight Kitchen
 Custom designs using standard cabinets



rtf systems™ Cabinets:	
QTY:	Item:
1 ea.	RTF60-29-AC
1 ea.	RTF24-29-AC
1 ea.	RTF36-29-RC

Finishing Materials:	
QTY:	Item:
75 sq. ft.	Veneer Material
33 sq. ft.	Countertop Material



Finishing materials quantities are estimates and provided for illustration purposes only. The quantities listed will vary based on the type of material chosen and should be verified prior to ordering.




"L" Shaped Kitchen With Bar and 45-degree Corner Cabinet

Custom designs using standard cabinets



rtf systems™ Cabinets:	
QTY:	Item:
1 ea.	RTF72-29-AC
1 ea.	RTF45c-29-CC
1 ea.	RTF36-29-RC
1 ea.	RTF36-29-AC
1 ea.	RTF72-BAR
1 ea.	RTF45c-BAR
2 ea.	RTF36-BAR

Finishing Materials:	
QTY:	Item:
104 sq. ft.	Veneer Material
48 sq. ft.	Countertop Material
27 sq. ft.	Bar-top Material




Finishing materials quantities are estimates and provided for illustration purposes only. The quantities listed will vary based on the type of material chosen and should be verified prior to ordering.

Outdoor Living

OUTDOOR FIREPLACES

rtf systems™
 Ready-To-Finish Outdoor Kitchen Systems

Traditional Fireplace




rtf systems™ Fire Feature Kit:	
QTY:	Item:
1 ea.	RTF-FPLkit-(Size)

Kits available with 36", or 42" wide fireplace insert. Fireplace designed to burn wood, however, optional vented and vent-free gas logs and accessories available.

Finishing Materials:	
QTY:	Item:
116 sq. ft.	Veneer Material
12 sq. ft.	Hearth & Cap Material
2.5 sq. ft.	Mantle Material

Finishing materials quantities are estimates and provided for illustration purposes only. The quantities listed will vary based on the type of material chosen and should be verified prior to ordering.

Linear Fireplace



rtf systems™ Fire Feature Kit:	
QTY:	Item:
1 ea.	RTF-FPLkit-Linear-(NG or LP)


Specify gas type in part number when ordering. See Through Convesion Kit also available. Requires 110v electrical service at unit.

Finishing Materials:	
QTY:	Item:
52 sq. ft.	Veneer Material
10 sq. ft.	Cap Material

Finishing materials quantities are estimates and provided for illustration purposes only. The quantities listed will vary based on the type of material chosen and should be verified prior to ordering.

rtf systems™
Ready-To-Finish Outdoor Kitchen Systems


Round Fire Pits



rtf systems™ Fire Feature Kit:	
QTY:	Item:
1 ea.	RTF-FPkit-RND(Size)

Kits available as 36", 42", 48", and 60" diameter.
Fire Pits designed as gas burning only (LP or NG).
NEVER BURN WOOD in this fire pit. Fire glass and/or lava rock are the preferred burn media.

Finishing Materials:		
Diameter:	Veneer Mat.	Cap Mat.
36 in.	15 sq. ft.	10 sq. ft.
42 in.	17 sq. ft.	13 sq. ft.
48 in.	19 sq. ft.	16 sq. ft.
60 in.	24 sq. ft.	24 sq. ft.




Burner-To-Edge Dimension "A":	
Diameter:	Dimension A:
36 in.	8.5 in.
42 in.	8.5 in.
48 in.	11.5 in.
60 in.	17.5 in.



rtf systems™ Fire Feature Kit:	
QTY:	Item:
1 ea.	RTF-FPkit-SQR(Size)

Kits available as 36", 42", 48", and 60" square. Fire Pits designed as gas burning only (LP or NG). NEVER BURN WOOD in this fire pit. Fire glass and/or lava rock are the preferred burn media.

Finishing Materials:		
Square:	Veneer Mat.	Cap Mat.
36 in.	18 sq. ft.	13 sq. ft.
42 in.	21 sq. ft.	16 sq. ft.
48 in.	24 sq. ft.	21 sq. ft.
60 in.	30 sq. ft.	31 sq. ft.



Burner-To-Edge Dimension "A":	
Square:	Dimension A:
36 in.	8.5 in.
42 in.	8.5 in.
48 in.	11.5 in.
60 in.	17.5 in.

Outdoor Living

OUTDOOR FIREPLACES (CONT.)

rtf systems™
Ready-To-Finish Outdoor Kitchen Systems


Linear Fire Pits




rtf systems™ Fire Feature Kit:	
QTY:	Item:
1 ea.	RTF-FPkit-RND(Size)

Kits available as 36", 42", 48", and 60" length. Fire Pits designed as gas burning only (LP or NG). NEVER BURN WOOD in this fire pit. Fire glass and/or lava rock are the preferred burn media.

Finishing Materials:		
Length:	Veneer Mat.	Cap Mat.
42 in.	16 sq. ft.	8 sq. ft.
48 in.	18 sq. ft.	9 sq. ft.
60 in.	23 sq. ft.	11 sq. ft.
72 in.	27 sq. ft.	13 sq. ft.



Burner-To-Edge Dimensions "A" & "B":		
Length:	Dimension A:	Dimension B:
42 in.	6 in.	6 in.
48 in.	6 in.	6 in.
60 in.	6 in.	6 in.
72 in.	6 in.	6 in.




rtf systems™ Fire Feature Kit:	
QTY:	Item:
1 ea.	RTF-FPkit-BAR-(Size)

Kits available as 48", and 60" diameter. Fire Pits designed as gas burning only (LP or NG). NEVER BURN WOOD in this fire pit. Fire glass and/or lava rock are the preferred burn media. Base dimensions are 29" x 29".

Finishing Materials:		
Diameter:	Veneer Mat.	Cap Mat.
48 in.	35 sq. ft.	16 sq. ft.
60 in.	35 sq. ft.	24 sq. ft.

Bar Table Fire Pits



Burner-To-Edge Dimension "A":	
Square:	Dimension A:
36 in.	8.5 in.
42 in.	8.5 in.
48 in.	11.5 in.
60 in.	17.5 in.

Appliance Cabinets:

Part Number:	Description	Weight (lbs.)	Width (in.)	Height (in.)	Depth (in.)
RTF6-29-FC	6" Wide x 29" Deep x 36" Tall Outdoor Kitchen Filler Cabinet	46	6	36	29
RTF12-29-FC	12" Wide x 29" Deep x 36" Tall Outdoor Kitchen Filler Cabinet	64	12	36	29
RTF18-29-AC	18" Wide x 29" Deep x 36" Tall Outdoor Kitchen Appliance Cabinet with Universal Slide-In Appliance Frame and Universal Storage Accessory Frame	86	18	36	29
RTF24-29-AC	24" Wide x 29" Deep x 36" Tall Outdoor Kitchen Appliance Cabinet with Universal Slide-In Appliance Frame and Universal Storage Accessory Frame	104	24	36	29
RTF30-29-AC	30" Wide x 29" Deep x 36" Tall Outdoor Kitchen Appliance Cabinet with Universal Slide-In Appliance Frame and Universal Storage Accessory Frame	108	30	36	29
RTF36-29-AC	36" Wide x 29" Deep x 36" Tall Outdoor Kitchen Appliance Cabinet with Universal Slide-In Appliance Frame and Universal Storage Accessory Frame	138	36	36	29
RTF36-29-RC	36" Wide x 29" Deep x 36" Tall Outdoor Kitchen Refrigeration Cabinet with Universal Refrigeration Appliance Frame	132	36	36	29
RTF36-29-PB	36" Wide x 29" Deep x 36" Tall Outdoor Kitchen Power Burner Cabinet with Universal Slide-In Appliance Frame and Universal Storage Accessory Frame	140	36	36	29
RTF42-29-AC	42" Wide x 29" Deep x 36" Tall Outdoor Kitchen Appliance Cabinet with Universal Slide-In Appliance Frame and Universal Storage Accessory Frame	160	42	36	29
RTF48-29-AC	48" Wide x 29" Deep x 36" Tall Outdoor Kitchen Appliance Cabinet with Universal Slide-In Appliance Frame and Universal Storage Accessory Frame	164	48	36	29
RTF48-29-KC	48" Wide x 29" Deep x 36" Tall Outdoor Kitchen Kamado Cabinet with Kamado Appliance Frame and Universal Storage Accessory Frame	154	48	36	29
RTF54-29-AC	54" Wide x 29" Deep x 36" Tall Outdoor Kitchen Appliance Cabinet with Universal Slide-In Appliance Frame and Universal Storage Accessory Frame	176	54	36	29
RTF60-29-AC	60" Wide x 29" Deep x 36" Tall Outdoor Kitchen Appliance Cabinet with Universal Slide-In Appliance Frame and Universal Storage Accessory Frame	202	60	36	29
RTF66-29-AC	66" Wide x 29" Deep x 36" Tall Outdoor Kitchen Appliance Cabinet with Universal Slide-In Appliance Frame and Universal Storage Accessory Frame	206	66	36	29
RTF72-29-AC	72" Wide x 29" Deep x 36" Tall Outdoor Kitchen Appliance Cabinet with Universal Slide-In Appliance Frame and Universal Storage Accessory Frame	224	72	36	29

Corner Cabinets & End Caps:

Part Number:	Description	Weight (lbs.)	Width (in.)	Height (in.)	Depth (in.)
RTF90c-29-CC	29" Wide x 29" Deep x 36" Tall Outdoor Kitchen 90 Degree Corner Cabinet	90	29	36	29
RTF90c-29-CC-RND	29" Wide x 29" Deep x 36" Tall Outdoor Kitchen 90 Degree Corner Cabinet With Outside Radius	110	29	36	29
RTF45c-29-CC	29" Deep x 36" Tall Outdoor Kitchen 45 Degree Cabinets	46	44	36	29
RTF-EndCap-RND	15" Wide x 29" Deep x 36" Tall Outdoor Kitchen Rounded End Cap	88	15	36	29

Bar & Backsplash Accessories:

Part Number:	Description	Weight (lbs.)	Width (in.)	Height (in.)	Depth (in.)
RTF6-BAR	12" Overhang Raised Bar & Backsplash Designed To Attach To The Back Of 6" Wide Filler Cabinet	5	6	7	14
RTF12-BAR	12" Overhang Raised Bar & Backsplash Designed To Attach To The Back Of 12" Wide Filler Cabinet	10	12	7	14
RTF18-BAR	12" Overhang Raised Bar & Backsplash Designed To Attach To The Back Of 18" Wide Appliance Cabinet	15	18	7	14
RTF24-BAR	12" Overhang Raised Bar & Backsplash Designed To Attach To The Back Of 24" Wide Appliance Cabinet	20	24	7	14
RTF30-BAR	12" Overhang Raised Bar & Backsplash Designed To Attach To The Back Of 30" Wide Appliance Cabinet	25	30	7	14
RTF36-BAR	12" Overhang Raised Bar & Backsplash Designed To Attach To The Back Of 36" Wide Appliance or Refrigeration Cabinet	30	36	7	14
RTF42-BAR	12" Overhang Raised Bar & Backsplash Designed To Attach To The Back Of 42" Wide Appliance Cabinet	35	42	7	14
RTF48-BAR	12" Overhang Raised Bar & Backsplash Designed To Attach To The Back Of 48" Wide Appliance Cabinet	40	48	7	14
RTF54-BAR	12" Overhang Raised Bar & Backsplash Designed To Attach To The Back Of 54" Wide Appliance Cabinet	45	54	7	14
RTF60-BAR	12" Overhang Raised Bar & Backsplash Designed To Attach To The Back Of 60" Wide Appliance Cabinet	50	60	7	14
RTF66-BAR	12" Overhang Raised Bar & Backsplash Designed To Attach To The Back Of 66" Wide Appliance Cabinet	55	66	7	14
RTF72-BAR	12" Overhang Raised Bar & Backsplash Designed To Attach To The Back Of 72" Wide Appliance Cabinet	60	72	7	14
RTF90c-BAR	12" Overhang Raised Bar & Backsplash Designed To Attach To The Back Of One Side Of 90 Degree Corner Cabinet	25	29	7	14
RTF90c-DBL-BAR	12" Overhang Raised Bar & Backsplash Designed To Attach To The Back Of Two Sides Of 90 Degree Corner Cabinet	60	35	7	14
RTF90c-DBL-BAR/BKSP-R	12" Overhang Raised Bar & Backsplash Combo Designed To Attach To The Back Of Two Sides Of 90 Degree Corner Cabinet With Bar On Right Hand Side	44	35	7	14
RTF90c-DBL-BAR/BKSP-L	12" Overhang Raised Bar & Backsplash Combo Designed To Attach To The Back Of Two Sides Of 90 Degree Corner Cabinet With Bar On Left Hand Side	44	35	7	14
RTF45c-BAR	12" Overhang Raised Bar & Backsplash Designed To Attach To The Back Of 45 Degree Corner Cabinet	40	48	7	14

Part Number:	Description	Weight (lbs.)	Width (in.)	Height (in.)	Depth (in.)
RTF6-BKSP	7" Tall Raised Backsplash Designed To Attach To The Back Of 6" Wide Filler Cabinet	2	6	7	2
RTF12-BKSP	7" Tall Raised Backsplash Designed To Attach To The Back Of 12" Wide Filler Cabinet	4	12	7	2
RTF18-BKSP	7" Tall Raised Backsplash Designed To Attach To The Back Of 18" Wide Appliance Cabinet	6	18	7	2
RTF24-BKSP	7" Tall Raised Backsplash Designed To Attach To The Back Of 24" Wide Appliance Cabinet	8	24	7	2
RTF30-BKSP	7" Tall Raised Backsplash Designed To Attach To The Back Of 30" Wide Appliance Cabinet	10	30	7	2
RTF36-BKSP	7" Tall Raised Backsplash Designed To Attach To The Back Of 36" Wide Appliance or Refrigeration Cabinet	12	36	7	2
RTF42-BKSP	7" Tall Raised Backsplash Designed To Attach To The Back Of 42" Wide Appliance Cabinet	14	42	7	2
RTF48-BKSP	7" Tall Raised Backsplash Designed To Attach To The Back Of 48" Wide Appliance Cabinet	16	48	7	2
RTF54-BKSP	7" Tall Raised Backsplash Designed To Attach To The Back Of 54" Wide Appliance Cabinet	18	54	7	2
RTF60-BKSP	7" Tall Raised Backsplash Designed To Attach To The Back Of 60" Wide Appliance Cabinet	20	60	7	2
RTF66-BKSP	7" Tall Raised Backsplash Designed To Attach To The Back Of 66" Wide Appliance Cabinet	22	66	7	2
RTF72-BKSP	7" Tall Raised Backsplash Designed To Attach To The Back Of 72" Wide Appliance Cabinet	24	72	7	2
RTF90c-BKSP	7" Tall Raised Backsplash Designed To Attach To The Back Of One Side Of 90 Degree Corner Cabinet	10	29	7	2
RTF90c-DBL-BKSP	7" Tall Raised Backsplash Designed To Attach To The Back Of Two Sides Of 90 Degree Corner Cabinet	20	29	7	2
RTF45c-BKSP	7" Tall Raised Backsplash Designed To Attach To The Back Of 45 Degree Corner Cabinet	16	48	7	2

**STEER****3-burner stainless steel built-in gas barbecue grill.****Standard Features:**

- ◆ 30,000 BTU's
- ◆ Warming rack
- ◆ Grease tray
- ◆ Built in trim kit
- ◆ Smoker box
- ◆ Stainless steel burners
- ◆ Dual lined hood
- ◆ Zinc knobs



Product Code	Description
BU06328	25" 3-Burner Stainless Steel Built-in Grill, Propane Gas
BU06329	25" 3-Burner Stainless Steel Built-in Grill, Natural Gas

OUTLAW**4-burner stainless steel built-in gas barbecue grill.****Standard Features:**

- ◆ 60,000 BTU's
- ◆ 304 stainless steel construction
- ◆ 4 porcelain coated bar burners
- ◆ Single piece dual lined hood
- ◆ Piezo igniters/zinc knobs
- ◆ Solid stainless steel grates
- ◆ Heavy duty thermometer
- ◆ Warming rack 210 sq. in.
- ◆ Cooking surface 810 sq. in.
- ◆ CSA approved



Product Code	Description
26038 LP	4-Burner 30" Stainless Steel Built-in Gas Barbecue Grill, Propane Gas
26039 NP	4-Burner 30" Stainless Steel Built-in Gas Barbecue Grill, Natural Gas

**ANGUS****4-burner stainless steel built-in gas barbecue grill with infrared back burner****Standard Features:**

- ◆ 16 gauge — 304 stainless steel
- ◆ 75,000 BTU's total cooking power
- ◆ Infrared burner 15,000 BTU's
- ◆ Five (5) bull sure-lite gas valves
- ◆ Five (5) Piezo igniters on each valve
- ◆ Heavy-duty thermometer
- ◆ Dual-lined roll top hood with seamless welded edges
- ◆ Stainless steel cooking grates 600 sq. in. cooking area
- ◆ Stainless steel warming rack 210 sq. in.
- ◆ Stainless steel rotisserie motor
- ◆ Chrome plated spit & rod
- ◆ Stainless steel full length handle
- ◆ Hose & regulator included with lp models
- ◆ N.G. regulator included with ng models
- ◆ CSA, SE, CE, approved

Product Code	Description
47628 LP	30 1/4" 4-Burner Stainless Steel Built-in Grill with Rotisserie & Lights, Propane Gas
47629 NP	30 1/4" 4-Burner Stainless Steel Built-in Grill with Rotisserie & Lights, Natural Gas



BRAHMA

5-burner stainless steel built in gas barbecue grill with infrared back burner

Standard Features:

- ◆ 16 gauge — 304 stainless steel
- ◆ Five cast stainless steel bar burners
- ◆ Infrared burner 15,000 BTU'S
- ◆ Six (6) bull sure-lite gas valves
- ◆ Six (6) Piezo igniters on each valve
- ◆ Heavy-duty thermometer
- ◆ Dual-lined roll top hood with seamless welded edges
- ◆ Stainless steel cooking grates 760 sq. in. cooking area
- ◆ Stainless steel warming rack 266 sq. in.
- ◆ Stainless steel full size drip tray
- ◆ Stainless steel rotisserie motor
- ◆ Chrome plated spit & rod
- ◆ Stainless steel full length handle
- ◆ Hose & regulator included with lp models
- ◆ N.G. regulator included with ng models
- ◆ CSA, SA, CE approved

Product Code	Description
575686 LP	38 1/4" 5-Burner Stainless Steel Built-in Grill with Rotisserie & Lights, Propane Gas
575686 NP	38 1/4" 5-Burner Stainless Steel Built-in Grill with Rotisserie & Lights, Natural Gas



7 BURNER PREMIUM GRILL

4-burner stainless steel built-in gas barbecue grill.

Standard Features:

- ◆ 105,000 BTU'S
- ◆ Smoker box
- ◆ Double sideburner 30,000 BTU'S
- ◆ Full length handle
- ◆ Warming rack
- ◆ Piezo igniters on each valve
- ◆ 800 sq. inches of cooking surface
- ◆ Four cast stainless burners
- ◆ Rotisserie included
- ◆ Heavy duty thermometer
- ◆ Dual lined roll top hood
- ◆ CSA, SA, CE approved

Product Code	Description
BU18038	46 3/4" 4-Burner Stainless Steel Built-in Grill with Rotisserie, Lights & Double Sideburner, Propane Gas
BU18039	Propane gas — 46 3/4" 4-Burner Stainless Steel Built-in Grill with Rotisserie, Lights & Double Sideburner, Natural Gas

ACCESSORIES - DOORS



Allows for entry into an island for the propane tank, gas lines, or whatever else you'd like to store inside your island.



Dimensions: 25 1/2" W X 18 1/4" H X 1 1/2" D

Cut Out Dimensions:

23" W X 15 3/4" H X 1 1/2" D

Product Code	Description
89970	Stainless Steel Single Door



Dimensions: 33" W X 22" H X 2" D

Cut Out Dimensions: 31" W X 19 3/4" H X 2 1/4" D

Product Code	Description
33568	Stainless Steel Double Door

ACCESSORIES - COMBOS



Adds a space saving design feature to any island.

Dimensions: 33" W X 22" H X 20 1/2" D

Cut Out Dimensions: 31" W X 19 1/2" H X 20 3/4" D

Product Code	Description
25876	Stainless Steel Door/Drawer Combo



Dimensions: 33" W X 22" H X 16 1/4" D

Cut Out Dimensions: 31" W X 19 3/4" H X 16 3/8" D

Product Code	Description
65784	Stainless Steel Door/Propane Drawer Combo

ACCESSORIES - DRAWERS

Cut Out Dimensions: 23 1/4" W X 4" L X 20 3/4" D

Product Code	Description
09970	Stainless Steel Single Drawer

Cut Out Dimensions: 12 3/4" W X 19 1/2" L X 20 3/4" D

Product Code	Description
56985	Stainless Steel Double Drawer

Cut Out Dimensions: 28 1/2" W X 10" L X 20 1/4" D

Product Code	Description
85747	Stainless Steel Warming Drawer



Outdoor Living

ACCESSORIES - REFRIGERATORS



- ◆ Space saving flush back design
- ◆ Stainless steel door panel
- ◆ Reversible door-left or right swing
- ◆ Full range temperature control
- ◆ Beverage can dispenser (Holds up to five 12 oz. cans)



Cut Out Dimensions: 21.5" W X 33" H X 20.75" D

Product Code	Description
11001	Stainless Steel Refrigerator

Cut Out Dimensions: 21.25" W X 34.5" L X 2" D

Product Code	Description
99935	Stainless Steel Refrigerator Frame

ACCESSORIES - SINKS

Dimensions: 15" L x 15" W

Cut Out Dimensions: 14 1/4" L X 14.25" W X 7 5/8" D



Product Code	Description
12389	Stainless Steel Sink

ACCESSORIES - ICE CHEST

Dimensions:

16 3/4" W X 21 1/2" D

Cut Out Dimensions:

14 1/4" W X 20 1/2" L X 15 1/2" D



Product Code	Description
00002	Stainless Steel Ice Chest

ACCESSORIES - BAR CENTERS



Dimensions:

18" W X 10 1/2" H X 25 3/4" D

Cut Out Dimensions:

17 1/8" W x 9 3/4" H x 22 1/4" D

Dimensions: 30" W X 10 1/2" H X 25 3/4" D

Cut Out Dimensions: 29" W X 9 3/4" H X 22 3/4" D



Product Code	Description
11001	Stainless Steel Refrigerator

ACCESSORIES - SIDE BURNERS

Stainless Steel Double Side Burner

- ◆ 30,000 BTU'S
- ◆ Piezo ignition
- ◆ Cast brass burner
- ◆ Porcelain cast iron grates



Cut Out Dimensions: 22 3/8" W X 17 1/8" L X 2 1/2" D

Product Code	Description
60088 LP	Propane – Stainless Steel Double Side Burner
60099 NG	Natural Gas – Stainless Steel Double Side Burner

Slide-in Double Side Burner, Front & Back

- ◆ 304 stainless steel
- ◆ 304 stainless steel removable cover
- ◆ Solid brass burners, 11,000 BTU'S each
- ◆ Solid stainless steel grates and Piezo igniter system



Cut Out Dimensions: 12 1/8" L X 20 1/2" W X 10" D


Product Code	Description
30008 LP	Propane – Slide in Double Side Burner, Front and Back
30009 NG	Natural Gas – Slide in Double Side Burner, Front and Back

ACCESSORIES - INFRARED SEARING BURNER

Dimensions: 26 1/2" W X 20 1/2" D

Cut Out Dimensions:

22 3/8" W X 2 1/2" H X 17 1/8" D




Product Code	Description
20505	Angus/Brahma
20506	Lonestar



POURED IN PLACE COUNTER TOP FORMS

Stegmeier's Counter Top Forms are the answer to installing the popular counters found in many contemporary kitchens, baths, and commercial sites such as restaurants and bars. These short 2" thick profiles are the perfect height for most applications and can be shaped or mitered to any angle.


any angle.



Counter Top Forms have a smooth even texture allowing them to be stripped early while there is ample time for finishing.

CARTON INCLUDES:

- 32" COUNTER TOP FORMS
- 1 COUNTER TOP SIDE KIT
(35 TIE WIRES, 25 WOOD SCREWS, 1 FOAM PROFILE EDGING TOOL)
- 1 ROLL OF BENDING TAPE




SETUP



POUR



FINISH



If 3 1/2" thick counters are desired see Pool Forms.